

Trainings ▾

Specifications

with Electronically Actuated Injector

Maximum fuel supply restriction at fuel pump inlet with dirty fuel filter element(s) at maximum fuel flow:

Industrial Applications	34 kPa [10 in-Hg]
-------------------------	-------------------

Marine Applications	34 kPa [10 in-Hg]
---------------------	-------------------

Maximum fuel drain restriction before (or without) check valve:

Industrial Applications	34 kPa [10 in-Hg]
-------------------------	-------------------

Marine Applications	34 kPa [10 in-Hg]
---------------------	-------------------

Maximum fuel inlet temperature:	71°C [160°F]
---------------------------------	--------------

Minimum fuel tank venting rate:	1700 liters/hr [60 cubic ft/hr]
---------------------------------	---------------------------------

with Mechanically Actuated Injector

Engine Idle Speed	650 to 725 rpm
-------------------	----------------

Maximum Fuel Inlet Restriction (at rated power)

Clean Fuel Filter	14 kPa [4 in-Hg]
-------------------	------------------

Maximum Fuel Inlet Restriction (at rated power)

Dirty Fuel Filter	27 kPa [8 in-Hg]
-------------------	------------------

Maximum Fuel Drain Line Restriction (at high idle, no load)

No Check Valves	8 kPa [2.5 in-Hg]
-----------------	-------------------

Check Valves	22 kPa [6.5 in-Hg]
--------------	--------------------

Fuel Check Valve between Fuel Filter and Fuel Pump

Minimum Opening Pressure	2.1 kPa [0.6 in-Hg]
--------------------------	---------------------

Fuel Check Valve between Fuel Pump and Cylinder Head

Opening Pressure	21 to 55 kPa [6.20 to 16.25 in-Hg]
------------------	------------------------------------

Fuel Check Valve in Fuel Drain Line

Opening Pressure	1.7 to 3.3 kPa [0.5 to 1 in-Hg]
------------------	---------------------------------

Minimum Engine Cranking Speed	150 rpm
-------------------------------	---------

Minimum Fuel Tank Air Venting Capability

With 8.5 kPa [2.5 in-Hg] or less fuel drain restriction	425 liter/hr [15 cubic ft/hr]
---	-------------------------------

Derate Engine Fuel Rate for High Altitude	4 percent per 300 m [1000 ft] above 3600 m [12,000 ft]
---	--

Derate Engine Fuel Rate for Hot Weather	2 percent per 11°C above 38°C [1 percent per 10°F above 100°F]
---	--

Shutoff Valve Solenoid Coil Resistance

12 VDC	6 to 10 ohms
--------	--------------

24 VDC	26 to 40 ohms
--------	---------------