

Trainings ▾

Specifications

Lubricating Oil Pressure, Main Oil Rifle (15W-40 oil at 107°C [225°F]):

Minimum at rated rpm	310 kPa [45 psi]
Maximum at rated rpm	483 kPa [70 psi]
Minimum at idle rpm	138 kPa [20 psi]
Maximum Lubricating Oil Pressure Spike on a Cold Engine	1655 kPa [240 psi]
Maximum Lubricating Oil Temperature	121°C [250°F]
Maximum Lubricating Oil Flow to All Accessories	57 liters/min [15 gpm]
Maximum Lubricating Oil Pan Sump Capacity	See Below

Eliminator Oil Capacity - Engine Operation:

QSK38/K38 and QSK50/K50	18 liters [4.8 gal] - 20 liters [5.3 gal]
-------------------------	---

Fleetguard™ Centrifuge - Engine Operation:

Centrifuge capacity	1 liter [0.26 gal]
---------------------	--------------------

Lubricating Oil Filter Capacity (each filter):

Model LF3365:	2.5 liters [0.67 gal]
---------------	-----------------------

Model LF9050:	2.5 liters [0.67 gal]
---------------	-----------------------

Combination Filter (four required on K38 and five required on K50)

Sump Configuration	System Capacity	
	Low Level	High Level
K38 Engine		
Sub-base Sump	87 liters [23 gal]	114 liters [30 gal]

Sump Configuration	System Capacity	
	Low Level	High Level
Double Deep Front/Center Sump	140 liters [37 gal]	166 liters [44 gal]
Double Deep Rear/Center Sump	140 liters [37 gal]	166 liters [44 gal]
QSK38 Engine		
Deep Center Sump	87 liters [23 gal]	114 liters [30 gal]
Deep Front Sump	140 liters [37 gal]	166 liters [44 gal]
Deep Rear Sump	140 liters [37 gal]	166 liters [44 gal]
Full Length	129 liters [34 gal]	186 liters [49 gal]
K50 Engine		
Sub-base Sump	171 liters [45 gal]	246 liters [65 gal]
Deep Center Sump	174 liters [46 gal]	204 liters [54 gal]
Front and Front/Center Sump	171 liters [45 gal]	246 liters [65 gal]
QSK50 Engine		
Deep Center Sump	174 liters [46 gal]	204 liters [54 gal]
Deep Front/Center and Deep Rear/Center Sump	121 liters [32 gal]	151 liters [40 gal]
Deep Rear/Deep Front Sump	121 liters [32 gal]	151 liters [40 gal]
Rear and Rear/Center Sump	174 liters [46 gal]	204 liters [54 gal]
Full Length Sump	171 liters [45 gal]	246 liters [65 gal]
Gas Compression		
Lubricating Oil Pressure at Rated Speed for Temperatures Above 82°C [180°F]	207 to 448 kPa [30 to 65 psi]	
Maximum Oil Consumption	0.47 liters/hr [0.50 qt/hr]	
Lubricating Oil Temperature - Maximum in Sump	110°C [230°F]	
High Capacity Lubricating Oil System		
High Oil Level	356 liters [94 gal]	
Low Oil Level	280 liters [74 gal]	
Lubricating Oil Pan		
High Oil Level	185 liters [49 gal]	
Low Oil Level	129 liters [34 gal]	

Lubricating Oil Reservoir Tank

Oil Level	151 liters [40 gal]
-----------	---------------------

Last Modified: 04-Mar-2014