

Trainings ▾

Specifications

with Mechanically Actuated Injector

Coolant Capacity (engine only)

KT38	104 liters [27.5 gal]
------	-----------------------

KTA38	118 liters [31.2 gal]
-------	-----------------------

KTA Marine (with heat exchanger)	155 liters [41 gal]
----------------------------------	---------------------

KTA Industrial and Generator	161 liters [42.5 gal]
------------------------------	-----------------------

KTA50 Marine	197 liters [52 gal]
--------------	---------------------

KTA50 Marine (with heat exchanger)	227 liters [60 gal]
------------------------------------	---------------------

Note : Maximum allowable draw down at 20 percent of system capacity (whichever is greater).

KT38, KTA38	21 liters [22.2 qt]
-------------	---------------------

KTTA38	23 liters [24.3 qt]
--------	---------------------

KTA50	26 liters [28 qt]
-------	-------------------

KTTA50, K2000	29 liters [31 qt]
---------------	-------------------

Engine Thermostat	82 to 94°C [180 to 202°F]
-------------------	---------------------------

Low Temperature Aftercooler Thermostat Range

	66 to 79°C [151 to 174°F]
--	---------------------------

Top Tank Coolant Temperature (maximum)

Standby Power-Generation	104°C [219°F]
--------------------------	---------------

Prime Power-Generation	100°C [212°F]
------------------------	---------------

Marine	96°C [205°F]
Industrial	95°C [203°F]
Top Tank Coolant Temperature (minimum)	70°C [158°C]
Maximum Coolant Pressure	
Without Pressure Cap	
KT38, KTA38, KTTA38	241 kPa [35 psi]
KTA50	283 kPa [41 psi]
KTTA50, K2000	345 kPa [50 psi]
With Pressure Cap (minimum)	
Marine	103 kPa [15 psi]
Non-Marine	48 kPa [7 psi]
Coolant Expansion Volume	
Percentage of system capacity (minimum)	5 percent
with Electronically Actuated Injector	
Engine Coolant Circuit	
Cooling System Type	2 Pump - 2 Loop
Minimum Operating Block Coolant Temperature	71°C [160°F]
Minimum Fill Rate	19 L/m [5 gpm]
Maximum Initial Fill Time	40 Minutes
Minimum Water Pump Inlet Pressure with Fully Deaerating Cooling System	34 kPa [10 in-Hg]
Maximum Static Head of Coolant Above Crankshaft Centerline	18.3 m [60 ft]
Minimum Pressure Cap Rating at Sea Level	76 kPa [11 psi]

Maximum Pressure Cap Rating at Sea Level	103 kPa [15 psi]
Minimum Coolant Expansion space (percentage of total cooling system capacity)	6 percent
Coolant Capacity - Engine only	140 liters [148 qt]
Coolant Capacity - Low Temperature Aftercooler	30 liters [32 qt]
Maximum Recommended External Coolant Flow Restriction in Engine Circuit	82.7 kPa [12 psi]
Engine Coolant Circuit Thermostat Opening Temperature	82°C [180°F]
Engine Coolant Circuit Thermostat Fully Open Temperature	94°C [201°F]
Maximum Allowable Deaeration Time	25 minutes
Acceptable types of deaeration systems	Fully Deaerating
Maximum Drawdown (percentage of total cooling system capacity)	11 percent
Low Temperature Aftercooler (LTA) Circuit	
Low Temperature Aftercooler Circuit Thermostat Opening Temperature	46°C [115°F]
Low Temperature Aftercooler Circuit Thermostat Fully Open Temperature	57°C [135°F]
Maximum Recommended External Coolant Restriction in LTA Circuit (1P-2L or 2P-2L)	82.7 kPa [12 psi]