

Trainings ▾

Fuel Recommendations

WARNING

Do not mix gasoline, alcohol, or gasohol with diesel fuel. This mixture can cause an explosion.

CAUTION

Due to the precise tolerances of diesel injection systems, it is extremely important that the fuel be kept clean and free of dirt or water. Dirt or water in the system can cause severe damage to both the fuel pump and the fuel injectors.

CAUTION

Lighter fuels can reduce fuel economy and can possibly damage the fuel injection pump.

Cummins recommends the use of ASTM Number 2D fuel. The use of Number 2D fuel will result in optimum engine performance.

At operating temperatures below 0°C [32°F], acceptable performance can be obtained by using blends of Number 2D and Number 1D.

The viscosity of the fuel **must** be kept above 1.3 cSt at 40°C [104°F] to provide adequate fuel system lubrication.

The following chart lists acceptable alternate fuels for C8.3 Series engines.

Acceptable Substitute Fuels - Cummins C8.3 Fuel System

Numb er 1D Diesel (1)(2)	Numb er 2D Diesel	Numb er 1K Keros ene	Jet-A	Jet-A1	JP-5	JP-8	Jet-B	JP-4	CITE
OK	OK	OK	OK	OK	OK	OK	NOT OK	NOT OK	NOT OK

Any adjustment to compensate for reduced performance with a fuel system using alternate fuel is **not** warrantable.

Winter blend fuels, such as those found at commercial fuel dispensing outlets, are combinations of Number 1D and Number 2D diesel fuel and are acceptable.

Additional information for fuel recommendations and specifications can be found in Fuel for Cummins Engines, Bulletin Number 3379001 (</qs3/pubsys2/xml/en/bulletin/3379001.html>). See the ordering information in the back of this manual.

Last Modified: 04-May-2007
