

Trainings ▾

Specifications

Industrial

BoreStrokeDisplacementEngine Weight (dry) with Standard AccessoriesWet WeightFiring Order	114 mm [4.49 in] 135 mm [5.32 in] 8.27 liters [504.7 C.I.D.] 603 to 612 kg [1330 to 1350 lb] 635 to 658 kg [1400 to 1450 lb] 1-5-3-6-2-4
---	--

Valve Clearances:

Intake 0.30 mm [0.012 in]Exhaust 0.61 mm [0.024 in]

Rotation, Viewed from the Front of the Engine	Clockwise
---	------------------

Compression Ratio:

Naturally Aspirated 16.4:1Turbocharged 17.3:1Turbocharged/Aftercooled 16.5:1Charge Air Cooled 18.0:1

Marine

TypeBore and StrokeDisplacement	Four cycle, in-line, six cylinder 114 mm [4.49 in] x 135 mm [5.32 in] 8.3 liters [504.5 C.I.D.]
---------------------------------	---

Engine Mounting:

Maximum Allowable Bending Moment at Rear Face of Block 1356 N•m [1000 ft-lb]Minimum/Maximum Static Installation Angle for In-line Drives (front up) 0 degrees/12 degreesMinimum/Maximum Static Installation Angle for V-Drives (front up) 3 degrees/12 degrees

Note : “Front up” refers to front of engines. In V-drives it faces the back of the boat.

Automotive

BoreStrokeDisplacementEngine Weight (dry) with Standard AccessoriesWet WeightFiring Order	114 mm [4.49 in] 135 mm [5.32 in] 8.27 liters [504.7 C.I.D.] 603 to 612 kg [1330 to 1350 lb] 635 to 658 kg [1400 to 1450 lb] 1-5-3-6-2-4
---	--

Valve Clearances:

Intake 0.30 mm [0.012 in]Exhaust 0.61 mm [0.024 in]

Rotation, Viewed from the Front of the Engine	Clockwise
---	------------------

Compression Ratio:

6C8.3 16.4:16CT8.3 17.3:16CTA8.3 16.5:1C8.3 17.3:1 (low torque) or 18:1 (high torque)

