

Trainings ▾

Specifications

Industrial Applications

Oil Pressure

At Idle Speed - Minimum	69 kPa [10 psi]
Normal Operating Speed	205 kPa to 517 kPa [30 psi to 75 psi]
Regulated Pressure	517 kPa [75 psi]
Maximum Allowable Temperature	120°C [250°F]

Maximum Operational Angularity of Oil Pan (see engine mounting)

Front Down	45 degrees
Front Up	35 degrees
Side to Side	45 degrees

Oil Capacity of Standard Engine:

Standard Oil Pan (Pan Only)	18.9 liters [20 qt]
Standard Oil Pan with Cylinder Block Stiffener Plate (Pan Only)	19.9 liters [21 qt]

Oil Pan Low to High:

Standard Oil Pan	15.1 to 18.9 liters [16 to 20 qt]
Standard Oil Pan with Cylinder Block Stiffener Plate	16.1 to 19.9 liters [17 to 21 qt]
Total System Capacity	19.9 liters [21 qt]
Total System Capacity (excluding bypass Filter)	21.9 liters [23.2 qt]

Note : Some applications have a slightly different oil pan capacity. Contact the local Cummins Distributor if there are any questions.

Marine Applications

Oil Pressure

At Idle Speed - Minimum	55 kPa [8 psi]
Normal Operating Range	205 to 517 kPa [30 to 75 psi]
Maximum Allowable Oil Temperature	120°C [250°F]
Oil Pan Capacity High/Low	17/13 liters [18/14 qt]
Total System Capacity (excluding bypass filter)	21.9 liters [23.2 qt]

Last Modified: 09-Jul-2012
