

Trainings ▾

Specifications

Industrial

Coolant Capacity (engine only)Standard Modulating Thermostat - RangeMaximum Allowable Operating TemperatureMinimum Recommended Operating TemperatureMinimum Recommended Pressure Cap	10.9 liters [11.5 qt] 84 to 91°C [184 to 195°F] 100°C [212°F] 70°C [158°F] 50 kPa [7 psi]
--	---

Marine

Coolant Capacity - Engine Only Coolant Capacity - Engine with Heat ExchangerMaximum External Pressure Loss in Cooling SystemMaximum Static Pressure of Coolant (exclusive of pressure cap)Standard Thermostat (modulating) RangeMaximum Coolant TemperatureMinimum Allowable Coolant Expansion SpaceMinimum Coolant Makeup CapacityMaximum Sea Water PressureMaximum Sea Water Inlet Restriction	12.3 liters [13 qt] 28.9 liters [30.5 qt] 35 kPa [5 psi] 103 kPa [15 psi] 71 to 83°C [160 to 181°F] 96°C [205°F] 5 percent of System Capacity 2.5 liters [2.6 qt] 172 kPa [25 psi] – 127 mm Hg [– 5 in Hg]
--	--

Automotive

Coolant Capacity (engine only) for 6C8.3, 6CT8.3, 6CTA8.3, C8.3Standard Modulating Thermostat - Range for 6C8.3, 6CT8.3, 6CTA8.3, C8.3Maximum Allowable Operating Temperature for 6C8.3, 6CT8.3, 6CTA8.3, C8.3Minimum Recommended Operating Temperature for 6C8.3, 6CT8.3, 6CTA8.3, C8.3Minimum Recommended Pressure Cap for 6C8.3, 6CT8.3, 6CTA8.3, C8.3	9.9 liters [10.5 qt] 81°C to 95°C [178°F to 203°F] 100°C [212°F] 70°C [158°F] 50 kPa [7 psi]
---	--

