

Trainings ▾

Specifications

12-VDC System

Minimum Recommended Battery Capacity:

Cold Cranking Amperes (CCA) Rating 1250 CCA
Marine Cranking Amperes (MCA) Rating 1563
MCA
Reserve Capacity (discharging 25 amps at 27°C [80°F]) 320 minutes

Maximum Allowable Resistance of Starting Circuit Maximum Allowable Voltage Drop of Starting Circuit Wiring Diagram Number	0.00075 ohms 0.075 VDC 3920281
---	--------------------------------------

24-VDC System

Minimum Recommended Battery Capacity:

Cold Cranking Amperes (CCA) Rating 625 CCA
Marine Cranking Amperes (MCA) Rating 781
MCA
Reserve Capacity (discharging 25 amps at 27°C [80°F]) 320 minutes

Maximum Allowable Voltage Drop of Starting Circuit Maximum Allowable Resistance of Starting Circuit Wiring Diagram Number	0.2 VDC 0.002 ohms 3920281
---	----------------------------------

Batteries (Specific Gravity)

Specific Gravity at 27°C [80°F]	State of Charge
1.260 to 1.280	100%
1.230 to 1.250	75%
1.200 to 1.220	50%
1.170 to 1.190	25%
1.110 to 1.130	Discharged

