

Trainings ▾

Specifications

Industrial

Recommended Battery Capacity				
System Voltage		Ambient Temperature		
	-18°C [0°F]		-29°C [-20°F]	
	Cold Cranking Amperes	Reserve Capacity (Minutes) ⁽¹⁾	Cold Cranking Amperes	Reserve Capacity (Minutes) ⁽¹⁾
12 VDC	1250	360	1875	360
24 VDC ⁽²⁾	625	180	900	180
The number of plates within a given battery size determines reserve capacity. Reserve capacity is the length of time for which a battery at 27°C [80°F] can supply 25 amperes at 10.5 volts or greater. CCA ratings are based on two 12-VDC batteries in series.				

Marine

12-VDC System

Minimum Recommended Battery Capacity:

Cold Cranking Amperes (CCA) Rating 1250 CCAMarine Cranking Amperes (MCA) Rating 1563 MCAReserve Capacity (discharging 25 amps at 27°C [80°F]) 320 minutes

Maximum Allowable Resistance of Starting CircuitMaximum Allowable Voltage Drop of Starting CircuitWiring Diagram Number	0.00075 ohms 0.075 VDC 3920281
---	--------------------------------

24-VDC System

Minimum Recommended Battery Capacity:

Cold Cranking Amperes (CCA) Rating 625 CCAMarine Cranking Amperes (MCA) Rating 781 MCAReserve Capacity (discharging 25 amps at 27°C [80°F]) 320 minutes

Maximum Allowable Voltage Drop of Starting Circuit Maximum Allowable Resistance of Starting Circuit Wiring Diagram Number	0.2 VDC 0.002 ohms 3920281
---	----------------------------

Auto

Recommended Battery Capacity				
System Voltage		Ambient Temperature		
	-18°C [0°F]		-29°C [-20°F]	
	Cold Cranking Amperes	Reserve Capacity (Minutes) ⁽¹⁾	Cold Cranking Amperes	Reserve Capacity (Minutes) ⁽¹⁾
12 VDC	1250	360	1875	360
24 VDC ⁽²⁾	625	180	900	180
The number of plates within a given battery size determines reserve capacity. Reserve capacity is the length of time for which a battery at 27°C [80°F] can supply 25 amperes at 10.5 volts or greater. CCA ratings are based on two 12-VDC batteries in series.				

Batteries (Specific Gravity)

Specific Gravity at 27°C [80°F]	State of Charge
1.260 to 1.280	100%
1.230 to 1.250	75%
1.200 to 1.220	50%
1.170 to 1.190	25%
1.110 to 1.130	Discharged