

Trainings ▾

Specifications

Note : Due to variations in rating of different engine models, refer to the specific engine data sheet for the particular engine model being tested.

Maintain the following limits during a chassis dynamometer test:

Intake Restrictions: (Maximum)

Clean Filter 380 mm H₂O [15 in H₂O] Dirty Filter 635 mm H₂O [25 in H₂O]

Air Inlet Temperature (Maximum) Exhaust Temperature	38°C [100°F] 700°C [1290°F]
---	-----------------------------

Exhaust Back Pressure: (Maximum)

Industrial 76 mm Hg [3.0 in Hg] EPA Certified 114 mm Hg [4.5 in Hg]

Smoke:

Bosch® Smoke Meter (Maximum) 2.5 Units Celesco Smoke Meter (Maximum) 4% Opacity

Coolant Temperature (Maximum) Lubricating Oil Temperature (Maximum)	100°C [212°F] 126.6°C [260°F]
---	-------------------------------

Lubricating Oil Pressure:

Low Idle (Minimum Allowable) 69 kPa [10 psi] Rated Speed (Minimum Allowable) 207 kPa [30 psi]

Fuel Filter Restriction: (Maximum)

Dirty Filter 89 mm Hg [3.5 in Hg]

Fuel Return Restriction (Maximum)	35 kPa [5 psi]
-----------------------------------	----------------

* Blowby:

6C8.3 (Maximum) New: 44 liters/minute; Worn: 88 liters/minute 6CT8.3 (Maximum) New: 113 liters/minute; Worn: 226 liters/minute 6CTA8.3 (Maximum) New: 113 liters/minute; Worn: 226 liters/minute

* The blowby checking tool, Part Number 3822566, has a special 7.67 mm [0.302 in] orifice that **must** be used to obtain an accurate reading.

Last Modified: 04-May-2007
