

Trainings ▾

Specifications

with Electronically Actuated Injector

For performance and fuel rate values, refer to the engine data sheet or the fuel pump code for the specific rating involved.

Engine Idle Speed	See Engine Data Sheet
-------------------	-----------------------

Fuel Inlet Maximum Restriction:

Dirty Fuel Filter	34 kPa [10 in-Hg]
-------------------	-------------------

Fuel Drain Line Restriction:

With Check Valves	127 mm-Hg [5 in-Hg]
-------------------	---------------------

With Check Valves Removed	254 mm-Hg [10 in-Hg]
---------------------------	----------------------

Water Removal:

Free	95 percent
------	------------

Emulsified	95 percent
------------	------------

Engine Minimum Cranking Speed	150 rpm
-------------------------------	---------

Marine Applications

Maximum Fuel Drain Line Restriction	34 kPa [10 in-Hg]
-------------------------------------	-------------------

Fuel Inlet Maximum Restriction (SeaPro™ Filters):

Dirty Fuel Filter	34 kPa [10 in-Hg]
-------------------	-------------------

with Mechanically Actuated Injector

For performance and fuel rate values, refer to the engine data sheet or the fuel pump code for the specific rating involved.

Engine Idle Speed	700 ± 25 rpm
-------------------	--------------

Maximum Fuel Inlet Restriction (at rated power):

Clean Fuel Filter	100 mm-Hg [4 in-Hg]
Dirty Fuel Filter	203 mm-Hg [8 in-Hg]
Maximum Fuel Drain Line Restriction (Industrial and Power-Generation only):	
Before Check Valves	254 mm-Hg [10 in-Hg]
After Check Valves	228 mm-Hg [9 in-Hg]
Maximum Fuel Drain Line Restriction (Marine only):	
Before Check Valves	304 mm-Hg [12 in-Hg]
After Check Valves and Before Fuel Cooler	279 mm-Hg [11 in-Hg]
Fuel Check Valve Between Fuel Pump and Electronic Fuel Control Valve Assembly (integral to fuel pump):	
Opening Pressure	14 to 21 kPa [2 to 3 psi]
Engine Minimum Cranking Speed	175 rpm
Fuel Check Valve in Fuel Drain Line:	
Opening Pressure	13 to 25 mm-Hg [0.5 to 1 in-Hg]
Derate Engine Fuel Rate for High Altitude	Refer to the engine performance curves and data sheets
Shutoff Valve Solenoid Coil Resistance in Ohms at 24-VDC	28 to 32 ohms
Fuel Pump Cranking Pressure	241 kPa [35 psi] at 175 rpm
Fuel Pump Pressure:	
1500 rpm (50 Hz)	1572 kPa [228 psi]
1800 rpm (60 Hz)	1820 kPa [264 psi]
1900 rpm	1896 kPa [275 psi]
2070 rpm	1896 kPa [275 psi]
2470 rpm	1896 kPa [275 psi]
Fuel Filter Specifications:	
Efficiency:	
at 10 microns	98.7 percent

at 8 microns	96 percent
at 5 microns	86 percent
Fuel Filter Specifications:	
Water Removal:	
Free	95 percent
Emulsified	95 percent