

Trainings ▾

Specifications

Lubricating Oil Pressure, Main Oil Rifle (15W-40 oil at 107°C [225°F]):

Minimum at rated rpm	310 kPa [45 psi]
----------------------	------------------

Maximum at rated rpm	483 kPa [70 psi]
----------------------	------------------

Minimum at idle rpm	138 kPa [20 psi]
---------------------	------------------

Lubricating Oil Pressure Spike on Cold Engine

Maximum	1724 kPa [250 psi]
---------	--------------------

Lubricating Oil Temperature

Maximum	120°C [248°F]
---------	---------------

Lubricating Oil Pan Sump

Capacity	See below
----------	-----------

Eliminator™ Oil Capacity - Engine Operation:

QSK45	18 liters [4.8 gal]
-------	---------------------

QSK60	20 liters [5.3 gal]
-------	---------------------

Fleetguard™ Centrifuge - Engine Operation:

Lubricating Oil Filter Capacity (each filter)(model LF9024):

Centrifuge capacity	1 liter [0.26 gal]
---------------------	--------------------

Combination filter (three required on QSK45, four required on QSK60)	2.65 liters [0.70 gal]
---	------------------------

Sump Configuration	System Capacity	
QSK45	Low Level	High Level
No Oil Sump	106 liters [28 gal]	130.5 liters [34.5 gal]
Front Sump	149.5 liters [39.5 gal]	174 liters [46 gal]
Center Sump	149.5 liters [39.5 gal]	174 liters [46 gal]
Rear Sump	149.5 liters [39.5 gal]	174 liters [46 gal]
Front and Center Sump	191 liters [50.5 gal]	216 liters [57 gal]

Center and Rear Sump	191 liters [50.5 gal]	216 liters [57 gal]
Full Length Sump	233 liters [61.5 gal]	257.5 liters [68 gal]
QSK60	Low Level	High Level
No Oil Sump	146 liters [38.5 gal]	176 liters [46.5 gal]
Rear Sump	149.5 liters [39.5 gal]	174 liters [46 gal]
Front and Center Sump	191 liters [50.5 gal]	261 liters [69 gal]
Center and Rear Sump	231 liters [61 gal]	261 liters [69 gal]
Center Sump	231 liters [61 gal]	261 liters [69 gal]
Full Length Sump – Small Capacity	231 liters [61 gal]	261 liters [69 gal]
Full Length Sump – Large Capacity	348 liters [92 gal]	378.5 liters [100 gal]

Last Modified: 25-Aug-2021
