

Trainings ▾

Specifications

QSK45 Engines

Coolant Capacity (engine only)	105 liters [28 gal]
Standard Modulating Thermostat Range	85 to 97°C [185 to 207°F]
Standard LTA Thermostat Range	46 to 57°C [115 to 135°F]
Maximum Allowable Top Tank Temperature (Industrial and Non-Prime Power-Generation only)	100°C [212°F]
Maximum Allowable Top Tank Temperature (Prime Power-Generation only)	104°C [220°F]
Minimum Recommended Top Tank Temperature	71°C [160°F]
Maximum Allowable Deaeration Time	25 minutes
Minimum Allowable Drawdown or 20 Percent of System Capacity (whichever is greater)	26 liters [7 gal]
Minimum Allowable Pressure Cap	76 kPa [11 psi]

QSK60 Engines

Coolant Capacity (Industrial and Power-Generation only):

Single-Stage	140 liters [37 gal]
Two-Stage	170 liters [45 gal]

Coolant Capacity (Marine only):

Engine only	233 liters [62 gal]
Engine with heat exchanger and expansion tank	318 liters [84 gal]

Standard Modulating Thermostat Range (with Mechanically Actuated Injectors)	85 to 97°C [185 to 207°F]
Standard Modulating Thermostat Range (with Electronically Actuated Injectors)	82 to 94°C [180 to 202°F]
Standard LTA Thermostat Range	46 to 57°C [115 to 135°F]
Maximum Allowable Top Tank Temperature (Industrial, Marine, and Non-Prime Power-Generation only)	100°C [212°F]
Maximum Allowable Top Tank Temperature (Prime Power-Generation only)	104°C [220°F]
Minimum Recommended Top Tank Temperature	71°C [160°F]
Maximum Allowable Deaeration Time	25 minutes
Minimum Allowable Drawdown or 20 Percent of System Capacity (whichever is greater)	28 liters [7.4 gal]
Allowable Pressure Cap Relief Range at Sea Level	76 to 103 kPa [11 to 15 psi]
Maximum Seawater Pump Outlet Pressure	206 kPa [30 psi]
Maximum Seawater Pressure Drop Across Heat Exchanger	138 kPa [20 psi]
Maximum Seawater Pump Inlet Restriction	255 mm Hg [8 in Hg]
Maximum Seawater Outlet Temperature	54°C [130°F]
Maximum Seawater Temperature Rise Across Heat Exchanger	22°C [40°F]
Minimum Seawater Temperature Rise Across Heat Exchanger	3°C [5°F]

