

Trainings ▾

Specifications

Minimum recommended battery capacity:

Engine Model	System Voltage	Temperature Range	Cold Cranking Amperes	Reserve Capacity	Maximum Allowable Starting Circuit Resistance
QSK45	24	-18 to 0°C [0 to 32°F]	1800	640 A	0.0020 ohms
QSK60	24	Above 0°C [32°F]	1800	640 A	0.0020 ohms
QSK60 Two-Stage	24	All	1800	640 A	0.0020 ohms

Battery Cable Sizes - American Wire Gauge (maximum length in cranking motor circuit):

24 to 32 VDC

Number 00	6.1 m [20 ft]
Number 000	8.2 m [27 ft]
Number 0000 or two Number 0 (see note)	6.1 m [20 ft]
Two Number 00	13.7 m [45 ft]

Note : Two strands of number 0 cable can be used instead of one number 0000 cable, provided all connections are carefully made to maintain equal current flow in each parallel cable.

Minimum Cranking Speed Without Starting Aid	150 rpm
---	---------

Starting aids, such as block heaters, lubricating oil pan heaters, and so forth, are available to aid in cold weather starting.

The number of plates within a given battery size determines reserve capacity. Reserve capacity is the length of time sustained cranking can occur.

CCA ratings are based on two 12 VDC batteries in series.

Batteries (Specific Gravity)

Battery State of Charge	Specific Gravity (at 27°C [80°F])
100 %	1.260 to 1.280
75%	1.230 to 1.250
50%	1.200 to 1.220
25%	1.170 to 1.190
DISCHARGED	1.110 to 1.130

Last Modified: 13-Jan-2021
