

## Trainings ▾

## Specifications

The following specifications are for a upright two-cylinder air compressor (Holset® ST676 Air Compressor Model)

|                                   |                                   |
|-----------------------------------|-----------------------------------|
| Cylinders                         | 2                                 |
| Compressor Capacity (at 1250 rpm) | 14.2 liter [30.00 cfm] per second |
| Piston Displacement               | 676 cc [41.3 C.I.D.]              |
| Bore                              | 92.08 mm [3.625 in]               |
| Stroke                            | 50.8 mm [2 in]                    |
| Speed                             | Engine speed                      |
| Cooling                           | Engine coolant                    |
| Lubrication                       | Engine lubricating oil            |

### Plumbing Line Sizes:

|                                         |                             |
|-----------------------------------------|-----------------------------|
| Coolant Inlet and Outlet (pipe fitting) | 12.7 mm NPTF [0.50 in NPTF] |
| Air Inlet (inside diameter)             | 22.22 mm [0.875 in]         |
| Air Outlet (minimum inside diameter)    | 15.88 mm [0.625 in]         |
| Height, Overall (approximate)           | 34.3 cm [13.5 in]           |
| Width, Overall (approximate)            | 17.8 cm [7 in]              |
| Length, Overall (approximate)           | 28.7 cm [11.30 in]          |
| Weight (approximate)                    | 33.5 kg [74.5 lb]           |

**Note :** In applications where duty cycles average 10 percent or more or air pressures are above 862 kPa [125 psi], use a discharge line with a minimum inside diameter of 15.9 mm [0.625 in] for single-cylinder compressors and 25.4 mm [1 in] for twin-

**cylinder compressors to prevent carbon buildup. Examples of these applications are as follows:**

- Refuse trucks
- Pickup and delivery trucks
- Transit buses
- Equipment with high accessory air usage.

The following specifications are for a upright single-cylinder air compressor (Holset® HD850 Air Compressor Models)

|                                         |                                  |
|-----------------------------------------|----------------------------------|
| Cylinders                               | 1                                |
| Compressor Capacity (at 1250 rpm)       | 7.1 liter [15.00 cfm] per second |
| Piston Displacement                     | 338 cc [20.63 C.I.D.]            |
| Bore                                    | 98.4 mm [3.875 in]               |
| Stroke                                  | 44.5 mm [1.75 in]                |
| Speed                                   | Engine speed                     |
| Cooling                                 | Engine coolant                   |
| Lubrication                             | Engine lubricating oil           |
| <b>Plumbing Line Sizes:</b>             |                                  |
| Coolant Inlet and Outlet (pipe fitting) | 9.53 mm NPTF [0.375 in NPTF]     |
| Air Inlet (inside diameter)             | 22.22 mm [0.875 in]              |
| Air Outlet (minimum inside diameter)    | 15.88 mm [0.625 in]              |
| Height, Overall (approximate)           | 31.1 cm [12.25 in]               |
| Width, Overall (approximate)            | 14.6 cm [5.75 in]                |
| Length, Overall (approximate)           | 22.9 cm [9 in]                   |
| Weight (approximate)                    | 18 kg [40 lb]                    |

