

Trainings ▾

General Information

WARNING

Do not mix gasoline, alcohol, or gasohol with diesel fuel. This mixture can cause an explosion.

CAUTION

Due to the precise tolerances of diesel injection systems, it is extremely important that the fuel be kept clean and free of dirt or water. Dirt or water in the system can cause severe damage to both the fuel pump and the injectors.

Cummins Inc. recommends the use of ASTM number 2 D fuel. The use of number 2 D fuel will result in optimum engine performance.

At operating temperatures below 0°C [32°F], acceptable performance can be obtained by using blends of number 2 D and number 1 D.

Note : Lighter fuels can reduce fuel economy.

The viscosity of the fuel **must** be kept above 1.3 cSt at 40°C [104°F] to provide adequate fuel system lubrication.

The following chart lists acceptable emergency fuels.

Acceptable Emergency Fuels - Cummins Fuel System
--

Numb er 1D Diesel	Numb er 2D Diesel	Numb er 1K Keros ene	Jet-A	Jet- A1	JP-5	JP-8	Jet-B	JP-4	CITE
1	OK	1	1	1	1	OK	NOT OK	NOT OK	NOT OK

1. OK
- only if fuel lubricity is adequate. Refer to Fuel for Cummins Engines, Bulletin 3379001 (/qs3/pubsys2/xml/en/bulletin/3379001.html).

Any
adjust
ment
to
comp
ensate
for
reduc
ed
perfor
mance
with a
fuel
syste
m
using
subsit
ute
fuel is
not
warra
ntable.

Additional information for fuel recommendations and specifications can be found in Fuel for Cummins Engines, Bulletin 3379001 (</qs3/pubsys2/xml/en/bulletin/3379001.html>). See ordering information in Section L.