

Trainings ▾

Specifications

Oil pressure, main rifle (15W-40 oil at 107°C [225°F])

Maximum at rated rpm	448 kPa [65 psi]
Minimum at rated rpm	245 kPa [36 psi]
Minimum at idle rpm	98 kPa [14 psi]
Maximum oil temperature	120°C [248°F]

Oil pan capacity:

Sump only	76 liters [20 gal]
Sump only	132 liters [35 gal]

Oil filter capacity (each filter):

Full-flow filter (four spin-on filters required)	2.65 liters [0.70 gal]
Bypass filter (two spin-on filters required)	2.27 liters [0.60 gal]
Venturi combo filter (four spin-on filters required)	2.52 liters [0.67 gal]

Total system capacity:

When using 75-liter [20-gal] oil pan	90 liters [24 gal]
When using 132-liter [35-gal] oil pan	148 liters [39 gal]

Note : The total lubricating oil system capacity is the summation of the oil pan capacity at the high mark on the dipstick, the full-flow or Venturi combination oil filter capacity, and the capacity of any bypass filters that are used.

Oil Sump Capacity			
Rated Sump Capacity	Sump Capacity at Low Level Mark on Dipstick in Liters [gal]	Sump Capacity at High Level Mark on Dipstick in Liters [gal]	Total System Capacity (Sump and Lube Filters) in Liters [gal]
76 liters [20 gal] oil pan	57 liters [15 gal]	76 liters [20 gal]	90 liters [24 gal]
132 liters [35 gal] oil pan	114 liters [30 gal]	132 liters [35 gal]	148 liters [39 gal]

Last Modified: 27-Aug-2014
