

## General Information

Tapered pipe plug fittings like National Pipe Thread (NPT) are designed to seal with an interference fit between the male and female thread form.

Interference caused by variables in materials (aluminum / cast iron or steel components), wall thickness, and differences in types of sealants change the amount of torque required to achieve the correct interference and will vary significantly between applications.

Use the recommended Torque Table for proper pipe plug installation.

| Torque Table   |                    |                                 |            |                                             |           |
|----------------|--------------------|---------------------------------|------------|---------------------------------------------|-----------|
| Pipe Plug Size |                    | Full Rotations After Hand Tight |            | Torque                                      |           |
| Thread         | Actual Thread O.D. | 1 Full Rotation = 360 Degrees   |            | In Aluminum / Cast Iron or Steel Components |           |
| in             | mm [ in ]          | Rotations                       | Degrees    | N•m                                         | ft-lb     |
| 1/16           | 8.1 [ 0.32 ]       | 1 to 2                          | 360 to 720 | 5 to 15                                     | 3 to 10   |
| 1/8            | 10.4 [ 0.41 ]      | 1 to 2                          | 360 to 720 | 15 to 20                                    | 10 to 15  |
| 1/4            | 13.7 [ 0.54 ]      | 1 to 2                          | 360 to 720 | 20 to 25                                    | 15 to 20  |
| 3/8            | 17.3 [ 0.68 ]      | 1 to 2                          | 360 to 720 | 25 to 35                                    | 20 to 25  |
| 1/2            | 21.6 [ 0.85 ]      | 1 to 2                          | 360 to 720 | 35 to 55                                    | 25 to 40  |
| 3/4            | 26.7 [ 1.05 ]      | 1 to 2                          | 360 to 720 | 45 to 75                                    | 35 to 55  |
| 1              | 33.5 [ 1.32 ]      | 1 to 2                          | 360 to 720 | 60 to 95                                    | 45 to 70  |
| 1-1/4          | 42.2 [ 1.66 ]      | 1 to 2                          | 360 to 720 | 75 to 115                                   | 55 to 85  |
| 1-1/2          | 48.3 [ 1.90 ]      | 1 to 2                          | 360 to 720 | 85 to 135                                   | 65 to 100 |