

Trainings ▾

General Information

Component	Wrench Size	N•m	ft-lb or in-lb
Aftercooler Mounting	10 mm	24	18 ft-lb
Aftercooler Water Hose Clamp	8 mm	5	44 in-lb
Alternator Link (Delco 10-15 SI)	13 mm	24	18 ft-lb
Alternator Link (Delco 20-27 SI)	3/4 in	43	32 ft-lb
Alternator Mtg. Bolt 10-15 SI	15 mm	43	32 ft-lb
Alternator Mtg. 27 SI	18 mm	77	57 ft-lb
Alternator Support (Upper)	10 mm	24	18 ft-lb
Belt Tensioner Flat Bracket	Allen 5 mm	24	18 ft-lb
Belt Tensioner Mounting	15 mm	43	32 ft-lb
Crankshaft Damper and Pulley	15 mm	137	101 ft-lb
Crossover Clamp	5/16 in	5	44 in-lb
Tee Bolt Type Clamp	11 mm	8	71 in-lb
Exhaust Outlet Pipe, V Band Clamp	7/16 in	8	71 in-lb
Fan Bracket Mounting	10 mm	24	18 ft-lb
Fan Pulley	10 mm	24	18 ft-lb
Fan Pulley	13 mm	43	32 ft-lb
Fuel Filter	75 to 85 mm	Install as specified by filter manufacturer	
Fuel Filter Adapter Nut	24 mm	32	24 ft-lb
Lubricating Oil Filter	75 to 85 mm	3/4 Turn after Contact	

Lubricating Oil Cooler Assembly	10 mm	24	18 ft-lb
Lubricating Oil Pan Drain Plug (steel)	17 mm	80	59 ft-lb
Lubricating Oil Pan Drain Plug (aluminum)	17 mm	30	22 ft-lb
Lubricating Oil Pan Heater Plug	27 mm	80	59 ft-lb
Lubricating Oil Pressure Regulator Plug	19 mm	80	59 ft-lb
Starter Mounting	10 mm	43	32 ft-lb
Thermostat Housing	10 mm	24	18 ft-lb
Water Inlet Connection	15 mm	43	32 ft-lb
Water Pump Mounting	13 mm	24	18 ft-lb
Rocker Lever Cover	15 mm	24	18 ft-lb
Water-in-Fuel Sensor	19 mm	Hand-Tighten	
Top - Load Filter Lid	10 mm	Hand-Tighten	

Last Modified: 25-Apr-2007
