

Trainings ▾

Specifications

Horsepower	Refer to engine dataplate
------------	---------------------------

Engine Weight (Dry) Less Flywheel and Electronics

B4.5 (naturally aspirated)	326 kg [721 lb]
----------------------------	-----------------

B4.5 and B3.9 (turbocharged)	338 kg [745 lb]
------------------------------	-----------------

B5.9	432 kg [952 lb]
------	-----------------

Compression Ratio	18:1
-------------------	------

Bore

B3.9 and B5.9	102 mm [4.02 in]
---------------	------------------

B4.5	107 mm [4.21 in]
------	------------------

Stroke

B3.9 and B5.9	120 mm [4.72 in]
---------------	------------------

B4.5	138 mm [5.42 in]
------	------------------

Displacement

B3.9	3.9 liters [238 C.I.D.]
------	-------------------------

B4.5	4.5 liters [275 C.I.D.]
------	-------------------------

B5.9	5.9 liters [359 C.I.D.]
------	-------------------------

Firing Order

B3.9 and B4.5	1-3-4-2
---------------	---------

B5.9	1-5-3-6-2-4
------	-------------

Valve Clearance

Intake	0.25 mm [0.010 in]
--------	--------------------

Exhaust	0.51 mm [0.020 in]
---------	--------------------

Crankshaft Rotation (viewed from the front of the engine)	Clockwise
---	------------------

Last Modified: 12-Dec-2019
