

Trainings ▾

Specifications

Oil Pressure

Low Idle (minimum allowed) 69 kPa [10 psi]At Rated Speed (minimum allowed) 207 kPa [30 psi]Regulated Pressure (B3.9, and B5.9) 345 kPa [50 psi]

Oil Capacity of Standard Engine

Standard - Pan Only

B3.9 9.5 liters [10 qt]B5.9 14.2 liters [15 qt]

Oil Capacity of Standard Engine

Total System

B3.9 10.9 liters [11.5 qt]B5.9 16.3 liters [17.2 qt]

Oil Capacity of Standard Engine

Deep Sump - Pan Only

B3.9 14.5 liters [15.3 qt]B5.9 24.0 liters [25.4 qt]

Oil Capacity of Standard Engine

Total System

B3.9 15.9 liters [16.8 qt]B5.9 26.1 liters [27.6 qt]

Oil Capacity of Standard Engine

Oil Pan Low - High - Standard Pan

B3.9 8.5 to 9.5 liters [9 to 10 qt]B5.9 12 to 14.2 liters [13 to 15 qt]

Oil Capacity of Standard Engine

Deep Sump

B3.9 11.5 to 14.5 liters [12.1 to 15.3 qt]B5.9 16.5 to 24.0 liters [17.4 to 25.4 qt]

Note : Some applications use a slightly different lubricating oil pan capacity. Contact a local Cummins Authorized Repair Facility if you have questions.

