

Trainings ▾

Specifications

Automotive Applications

Oil Pressure:

Low Idle (minimum allowable)	70 kPa [10 psi]
At 1200 rpm or Peak Torque (minimum allowable)	207 kPa [30 psi]

Oil Capacity of Standard Engine: Combination Filter:

LF9070	3.0 liters [0.8 gal]
LF9031, LF14000NN	2.6 liters [0.69 gal]

Oil Capacity of Standard Engine: Automotive:

Oil Pan (high-low)	34 to 26.5 liters [9 to 7 gal]
--------------------	--------------------------------

Oil Capacity of Standard Engine: Transit Bus:

Oil Pan (high-low)	34 to 30.2 liters [9 to 8 gal]
--------------------	--------------------------------

Oil Drain Fitting

Length	63.50 mm [2.500 in]
Diameter	41.28 mm [1.625 in]
Weight	0.363 kg [0.80 lb]

Marine Applications

Oil Pressure

Minimum at Idle	69 kPa [10 psi]
Operating Range	207 to 448 kPa [30 to 65 psi]

at torque peak or 1200 rpm (minimum allowable)	207 kPa [30 psi]
Oil Temperature	
Maximum	121°C [250°F]
Oil Pan Capacity	
Low	26.5 liters [7 gal]
High	30.3 liters [8 gal]
Total System Capacity:	
With engine Mounted Filter (combination NanoNet® filter holds 2.6 liters [0.69 gal])	37 liters [9.8 gal]
With Remote Mounted Filter	38 liters [10 gal]
Maximum Operational Angularity of Oil Pan Front Down:	
Rear Sump	30 degrees
Front Sump	45 degrees
Maximum Operational Angularity of Oil Pan Rear Down:	
Rear Sump	25 degrees
Front Sump	27 degrees
Maximum Operational Angularity of Oil Pan Side to Side:	
Rear Sump	30 degrees
Front Sump	42 degrees
Industrial and Power Generation	
Oil Pressure	
Minimum at Idle	69 kPa [10 psi]
Operating Range	207 to 448 kPa [30 to 65 psi]
at torque peak or 1200 rpm (minimum allowable)	207 kPa [30 psi]
Oil Temperature	

Maximum	
Industrial	121°C [250°F]
Generator Drive	135°C [275°F]
Oil Pan Capacity	
Industrial Applications	
Low	26.5 liters [7 gal]
High	34 liters [9 gal]
Total System Capacity:	
With engine Mounted Filter (combination NanoNet® holds 2.6 liters [0.69 gal])	37 liters [9.8 gal]
With Remote Mounted Filter	38 liters [10 gal]
Maximum Operational Angularity of Oil Pan – Industrial and Generator Drive (Rear Sump) –Varies by oil pan option - example numbers are based on stamped steel pan.	
Front Down:	
Rear Sump	42 degrees
Front Sump	45 degrees
Maximum Operational Angularity of Oil Pan – Industrial and Generator Drive (Rear Sump)	
Rear Down:	
Rear Sump	45 degrees
Front Sump	45 degrees
Maximum Operational Angularity of Oil Pan – Industrial and Generator Drive (Rear Sump)	
Side to Side:	
Rear Sump	45 degrees
Front Sump	35 degrees

