

Trainings ▾

Specifications

Coolant Capacity:

Engine with Heat Exchanger	29.4 liters [8 gal]
Minimum Drawdown	15.2 liters [4 gal]
Standard Thermostat Modulating Range	71 to 79.4°C [106 to 175°F]

Block coolant Pressure with Closed Thermostat (pressure cap removed)

Maximum	246 kPa [36 psi]
---------	------------------

Coolant Inlet Pressure with Open Thermostat and No Cap:

Minimum	64 mm Hg [2.5 in Hg]
Maximum Coolant Temperature	96°C [205°F]
Minimum Fill Rate	18.9 liters/min [5 gpm]
Minimum Initial Fill Time	2 minutes
Maximum Deaeration Time	10 minutes

Minimum Coolant Expansion Space:

Percent of Cooling system	5%
---------------------------	----

External Pressure Loss in Cooling System:

Maximum	35 kPa [5 psi]
---------	----------------

Static Pressure of Coolant:

Maximum - Exclusive of Pressure Cap	103 kPa [15 psi]
Maximum Sea Water Pressure	103 kPa [15 psi]
Maximum Sea Water Pump Inlet Restriction	-127 mm Hg [5 in Hg]
Maximum Sea Water Pump Initial Suction Lift	3 m [10 ft]
Pressure Cap Rating (with heat exchanger)	103 kPa [15 psi]

Maximum Allowable Coolant Flow to Accessories	37.9 liters/min [10 gal/min]
---	------------------------------

Last Modified: 01-May-2012
