

Trainings ▾

Specifications

Automotive Applications

Maximum Intake Restriction (Clean Air Filter Element)	254 mm H ₂ O [10.0 in H ₂ O]
---	--

Maximum Intake Restriction (Dirty Air Filter Element)	635 mm H ₂ O [25.0 in H ₂ O]
---	--

Maximum Temperature Rise Between Ambient Air and Engine Inlet Air

With EGR - Ambient (Above 0° [32°F])	11.1°C [20°F]
--------------------------------------	---------------

Without EGR - Ambient (Above 0° [32°F])	17°C [30°F]
---	-------------

Maximum Allowable Pressure Drop From Turbocharger to Intake Manifold	152 mm Hg [6 in Hg]
--	---------------------

Maximum Allowable Pressure Drop Across Charge Air Cooler	76 mm Hg [3 in Hg]
--	--------------------

Marine Applications

Maximum Intake Restriction (Clean Element)	254 mm H ₂ O [10 in H ₂ O]
--	--

Maximum Intake Restriction (Dirty Element)	507 mm H ₂ O [20 in H ₂ O]
--	--

Maximum Intake Manifold Temperature	49°C [120°F]
-------------------------------------	--------------

Maximum Engine Room Temperature:

Intake air Versus Ambient Air at Rated Condition	35°C [63°F] difference
--	------------------------

Industrial Applications

Maximum Intake Restriction (Clean Element)	381 mm H ₂ O [15 in H ₂ O]
--	--

Maximum Intake Restriction (Dirty Element)	635 mm H ₂ O [25 in H ₂ O]
--	--

Maximum Temperature Rise Between Ambient Air and Engine Inlet Air:

Ambient above 0°C [32°F]	35°C [63°F] difference
Generator Set Applications	
Maximum Intake Air Restriction Including Air Filter Plumbing	
Clean Filter Element	635 mm H ₂ O [25 in H ₂ O]
Dirty Filter Element	381 mm H ₂ O [15 in H ₂ O]
Maximum Allowable Pressure Drop from Turbocharger Outlet to Intake Manifold	
1500 rpm	2.5 in Hg [64 mm Hg]
1800 rpm	4 in Hg [102 mm Hg]
Maximum Temperature Rise Between Engine Air Inlet and Intake Manifold	25°C [45°F]

Last Modified: 05-Apr-2011
