

Trainings ▾

Specifications

Automotive Applications

Maximum Back Pressure at Turbocharger:

With CM875 or Combined CM870 and CM570	76 mm Hg [3 in Hg]
With CM876	305 mm Hg [12 in Hg]
With CM875 or Combined CM870 and CM570	1016 mm H ₂ O [40 in H ₂ O]
With CM876	4145 mm H ₂ O [163 in H ₂ O]
Exhaust Pipe Size (normally acceptable inside diameter)	86 mm [3.38 in]
Exhaust Pipe Size (normally acceptable outside diameter)	89 mm [3.5 in]

Transit Bus

Hg	152 mm Hg [6 in Hg]
H ₂ O	2082 mm H ₂ O [82 in H ₂ O]
Exhaust Pipe Size (normally acceptable inside diameter)	127 mm [5 in]

Marine Applications

Exhaust Pipe Size (normally acceptable inside diameter)	102 mm [4 in]
---	---------------

Maximum Exhaust Pipe Restriction

H ₂ O	1016 mm H ₂ O [40 in H ₂ O]
Hg	75 mm Hg [3in Hg]

Industrial and Generator Drive

Exhaust Pipe Size (normally acceptable inside diameter)	102 mm [4 in]
Maximum Exhaust Pipe Restriction	
H ₂ O	1016 mm H ₂ O [40 in H ₂ O]
Hg	75 mm Hg [3 in Hg]