

Trainings ▾

Specifications

Holset® SS296/SS296E/QE296 A/C Models

Cylinders	1
Compressor Swept Volume @ 1250 rpm	6.2 L per sec. [13.20 cfm]
Piston Displacement	296 cc [18.06 C.I.D.]
Bore	92.08 mm [3.625 in]
Stroke	44.45 mm [1.750 in]
Speed	Engine Speed
Cooling	Engine Coolant
Lubrication	Engine Lubricating Oil

Plumbing Line Sizes:

Coolant Inlet and Outlet (pipe fitting)	0.375-in NPTF
Air Inlet (inside diameter)	22.22 mm [0.875 in]
Air Outlet (minimum inside diameter)	12.7 mm [0.50 in]
Height, Overall (approximate)	31.1 cm [12.25 in]
Width, Overall (approximate)	14.6 cm [5.75 in]
Length, Overall (approximate)	22.9 cm [9.00 in]
Weight (approximate)	18 kg [40.0 lb]

Holset® ST676 A/C Model

Cylinders	2
Compressor Swept Volume @ 1250 rpm	14.2 l per sec. [30.00 cfm]

Piston Displacement	676 cc [41.3 C.I.D.]
Bore	92.08 mm [3.625 in]
Stroke	50.8 mm [2.00 in]
Speed	Engine Speed
Cooling	Engine Coolant
Lubrication	Engine Lubricating Oil

Plumbing Line Sizes:

Coolant Inlet and Outlet (pipe fitting)	0.50-in NPTF
Air Inlet (inside diameter)	22.22 mm [0.875 in]
Air Outlet (minimum inside diameter)	15.88 mm [0.625 in]
Height, Overall (approximate)	34.3 cm [13.50 in]
Width, Overall (approximate)	17.8 cm [7.00 in]
Length, Overall (approximate)	28.7 cm [11.30 in]
Weight (approximate)	33.5 kg [74.50 lb]

Note : In applications where duty cycles average 10 percent or more or air pressures are above 862 kPa [125 psi], use a discharge line with a minimum inside diameter of 15.9 mm [0.625 in] for single-cylinder compressors and 25.4 mm [1.00 in] for twin-cylinder compressors to prevent carbon buildup. Examples of these applications are as follows: refuse trucks, pickup and delivery trucks, transit buses, and equipment with high accessory air usage.

Holset® SS338/QE338 A/C Models

Cylinders	1
Compressor Swept Volume @ 1250 rpm	7.1 l per sec. [15.0 cfm]
Piston Displacement	338 cc [20.63 C.I.D.]
Bore	98.4 mm [3.875 in]
Stroke	44.5 mm [1.75 in]
Speed	Engine Speed

Cooling	Engine Coolant
Lubrication	Engine Lubricating Oil
Plumbing Line Sizes:	
Coolant Inlet and Outlet (pipe fitting)	0.375-in NPTF
Air Inlet	22.22 mm [0.875 in]
Air Outlet	12.7 mm [0.50 in]
Height, Overall (approximate)	31.1 cm [12.25 in]
Width, Overall (approximate)	14.6 cm [5.75 in]
Length, Overall (approximate)	22.9 cm [9.00 in]
Weight (approximate)	18 kg [40.0 lb]
Cummins	
Cylinders	1
Compressor Swept Volume @ 1250 RPM	6.6 L per sec. [14.0 CFM]
Piston Displacement	318 cc [19.405 C.I.D.]
Bore	85 mm [3.346 in]
Stroke	56 mm [2.204 in]
Speed	Engine Speed
Cooling	Engine Coolant
Lubricating	Engine Lubricating Oil
Plumbing Line Sizes:	
Coolant Inlet and Outlet (Pipe Fitting)	0.75-16 STOR(Straight thread o-ring)
Air Inlet (Inside Diameter)	20 mm [0.7874 in]
Air Outlet (Minimum Inside Diameter)	M27 x 2 STOR
Unloader port	M10 x 1 STOR
Govenor mounting (direct)	M8 x 1.25

Height, Overall (Approximate)	217.4 mm [8.559 in]
Width, Overall (Approximate)	142 mm [5.590 in]
Length, Overall (Approximate)	216 mm [8.503 in]
Weight (Approximate)	15 Kg [35.0 lbs]

Cummins 18.7 CFM Model

Cylinders	1
Compressor Swept Volume at 1250	6.6 l/sec. [140 cfm]
Piston Displacement	318 cc [19.405 C.I.D.]
Bore	85 mm [3.346 in]
Stroke	56 mm [2.205 in]
Speed	Engine speed
Cooling	Engine coolant
Lubrication	Engine lubricating oil

Plumbing Line Sizes:

Coolant Inlet and Outlet	3/4 x 16 STOR
Air Inlet	1-in nominal hose
Air Outlet	M27 x 2 STOR
Unloader Port	M10 x 1 STOR
Governor Mounting Direct	M8 x .25

Height, Overall (approximate)	217.4 mm [8.559 in]
Width, Overall (approximate)	142 mm [5.591 in]
Length, Overall (approximate)	216 mm [8.504 in]
Weight (approximate)	15 kg [33.0 lb]

Cummins 37.4 CFM Model

Cylinders	1
Compressor Swept Volume at 1250	15.5 l/sec. [35.5 cfm]
Piston Displacement	636 cc [39 C.I.D.]
Bore	85 mm [3.35 in]
Stroke	56 mm [2.2 in]
Speed	Engine speed
Cooling	Engine coolant
Lubrication	Engine lubricating oil
Plumbing Line Sizes:	
Coolant Inlet and Outlet	3/4 x 16 STOR
Air Inlet	1-in nominal hose
Air Outlet	M27 x 2 STOR
Unloader Port	M10 x 1 STOR
Governor Mounting Direct	M8 x .25
Height, Overall (approximate)	306 mm [12 in]
Width, Overall (approximate)	142 mm [5.6 in]
Length, Overall (approximate)	286.7 mm [11.29 in]
Weight (approximate)	17.24 kg [38 lb]