

Trainings ▾

Specifications

Automotive with CM870

Maximum Allowable Restriction to Pump With or Without Fuel Cooler:

With Clean Filter 203 mm Hg [8 in Hg] With Dirty Filter 305 mm Hg [12 in Hg]

Maximum Allowable Fuel Return Line Restriction	229 mm Hg [9 in Hg] 2.0 m ³ /hr [70 ft ³ /hr] 71°C [160°F] 6 to 10 ohms 517 kPa [75 psi]
Minimum Allowable Fuel Tank Vent Capability	
Maximum Allowable Fuel Inlet Temperature	
Fuel Shutoff Solenoid Resistance	
Maximum Allowable Pressure Drop Across Pressure Fuel Filter	

Automotive, Industrial with CM570 and Power Generation without CM570

Maximum Allowable Fuel Return Line Restriction

With Check Valve 165 mm Hg [6.5 in Hg] Without Check Valve 229 mm Hg [9 in Hg]

Minimum Allowable Fuel Tank Vent Capability	2.0 m ³ /hr [70 ft ³ /hr] 71°C [160°F] 6 to 10 ohms
Maximum Allowable Fuel Inlet Temperature	
Fuel Shutoff Solenoid Resistance	

Maximum Allowable Inlet Restriction at the IFSM - high idle, no load:

Upper Location 355 mm Hg [14 in Hg] Lower Location 305 mm Hg [12 in Hg]

Maximum Allowable Inlet Restriction at OEM Fuel Inlet:

Without Remote Mount Filter 76 mm Hg [3 in Hg] With Remote Mount Filter 254 mm Hg [10 in Hg]