

Trainings ▾

General Information

Cummins Inc. recommends the use of fully-formulated antifreeze or coolant containing a precharge of supplemental coolant additive (SCA). The antifreeze or coolant **must** meet the specifications outlined in the Technology and Maintenance Council (TMC) Recommended Practice (RP) 329 (ethylene glycol) or Recommended Practice (RP) 330 (propylene glycol). The use of fully-formulated antifreeze or coolant significantly simplifies cooling system maintenance.

Copies of Technology and Maintenance Council (TMC) specifications can be obtained through Cummins Inc., or by contacting:

Technology and Maintenance Council

American Trucking Association

2200 Mill Road

Alexandria, VA 33314-5388

Phone: (703) 838-1763

Fax (703) 836-6070

Fully-formulated antifreeze contains balanced amounts of antifreeze, SCA, and buffering compounds, but does **not** contain 50 percent water. Fully-formulated coolant contains balanced amounts of antifreeze, SCA, and buffering compounds already premixed 50/50 with deionized water.

The following pages explain water, antifreeze, and SCA's and how to test antifreeze and SCA levels.

This section also contains information on cooling system maintenance and a coolant treatment chart that is used to determine the correct SCA service filter.

Alternative maintenance practices for cooling systems can be found in Cummins® Coolant Requirements and Maintenance, Bulletin 3666132.

Specifications

Industrial Applications

Coolant Capacity

Engine only	24 liters [25 qt]
Standard Modulating Thermostat	
Temperature Range	82 to 93°C [180 to 200°F]
Maximum Coolant Pressure (exclusive of pressure cap - closed thermostat at the maximum no-load governed speed)	
All ratings	227 kPa [33 psi]
Coolant Alarm Activation Temperature	
Ratings Below 565 Horsepower	107°C [225°F]
Ratings of 565/600 Horsepower	110°C [230°F]
Maximum Allowable Top Tank Temperature	
Ratings Below 565 Horsepower	107°C [225°F]
Ratings of 565/600 Horsepower	110°C [230°F]
Power Generation, Standby	110°C [230°F]
Power Generation, Prime	104°C [220°F]
Minimum Recommended Top Tank Temperature	
Minimum Temperature	70°C [160°F]
Minimum Allowable Draw Down	
Minimum Allowable Draw Down	2.4 liters [2.5 qt] or 10 Percent of System Capacity (whichever is greater)
Minimum Recommended Pressure Cap	
Industrial	103 kPa [15 psi]
Power Generation	69 kPa [10 psi]
Minimum Fill Rate	
Without Low-Level Alarm	19 liters/min [5 gpm]
Maximum Deaeration Time	
Time	25 minutes
Fan-on Coolant Temperature	
Temperature	95°C [203°F]
Fan-on Intake Air Temperature	
Temperature	88°C [190°F]

Shutter Opening Temperature

Coolant	85°C [185°F]
Intake Air	60°C [140°F]