

Trainings ▾

Specifications

Fleetguard® filters are manufactured by Cummins Filtration Inc., which is a subsidiary of Cummins Inc. Fleetguard® filters are developed through joint testing at Cummins Inc. and at Cummins Filtration Inc. Fleetguard® filters are standard on new Cummins® engines. Cummins Inc. recommends their use.

Fleetguard® products meet all Cummins Inc. Source Approval Test standards to provide the quality filtration necessary to achieve the engine's design life. If other brands are substituted, the purchaser **must** insist on products that the supplier has tested to meet Cummins Inc. high quality standards.

Cummins Inc. can **not** be responsible for problems caused by nongenuine filters that do **not** meet Cummins Inc. performance or durability requirements.

Cummins Inc. requires a lubricating oil filter be used that meets Cummins Inc. Source Approval Method 10,765.

Filter Type	
Lubricating Oil Filter	
Cummins® Part Number	2882673 and 2882674
Fleetguard® Part Number	LF9070 and LF14000NN
Fuel-Water Separator	
Cummins® Part Number	4010650 and 4010651
Fleetguard® Part Number	FS1007 and FS1040
Coolant Filter	
Fleetguard® Part Number	WF2125 ¹
	WF2126 ²
	WF2127 ³
Crankcase Breather Filter	
Cummins® Part Number	3102738

1. This filter is designed for use with Fleetguard® extended service cooling system, which extends cooling system service to 1 year, 241,402 km [150,000 mi], or 4000 hours, whichever comes first. This filter is used for cooling systems up to 76 liters [20 gal]. Refer to Cummins® Coolant Requirements and Maintenance, Bulletin 3666132. Fleetguard® ES coolant **must** be used for all fill and top-off, which is critical for extended cooling system maintenance intervals.

2. This filter is designed for extended service intervals up to 80,467 km [50,000 mi] when using TMC RP329 or RP330 coolants and is used for cooling systems up to 76 liters [20 gal]. Refer to Cummins® Coolant Requirements and Maintenance, Bulletin 3666132. (</qs3/pubsys2/xml/en/bulletin/3666132.html>)
3. This filter has been designed for extended service intervals of 80,467 to 241,402 km [50,000 to 150,000 mi]. It has no chemical additives and can be used in the following systems:
 - Cooling systems above 76 liters [20 gal] in capacity.
 - See maintenance chart below.

When using WF2127 filter, the following volumes of treatment **must** be added at the designated distances:

Cooling System Capacity	80,467 km [50,000 mi] Service Interval with RP329/330 Coolant or Treated Water (Fleetcool or DCA4)	241,402 km [150,000 mi] Service Interval with ES Coolant (ES Liquid)
0 to 76 liters [0 to 20 gal]	0.95 liters [1 qt] (10 units)	0.95 liters [1 qt] (15 units)
76 to 151 liters [20 to 40 gal]	1.89 liters [2 qt] (20 units)	1.89 liters [2 qt] (30 units)
151 to 227 liters [40 to 60 gal]	2.84 liters [3 qt] (30 units)	2.84 liters [3 qt] (45 units)
227 to 303 liters [60 to 80 gal]	3.79 liters [4 qt] (40 units)	3.79 liters [4 qt] (60 units)
303 to 379 liters [80 to 100 gal]	0.94 liters [5 qt] (50 units)	0.94 liters [5 qt] (75 units)

Note : Filters **must** meet Cummins Inc. Source Approval Method 10,769. Fleetguard® filters meet Cummins Inc. Source Approval Method 10,769. The standard filter for the Signature™ engine is Fleetguard® WF2126. For systems larger than 379 liters [100 gal], use 0.94 liters [1 qt] per 57 liters [15 gal]. Consult vehicle manufacturer for total cooling system capacity.