

Trainings ▾

Specifications

Oil Pressure

Low idle (minimum allowed)	124 kPa [18 psi]
At rated (minimum allowed)	207 kPa [30 psi]
High-pressure dump valve opening pressure range	900 kPa [131 psi] to 1100 kPa [160 psi]
Main rifle regulating valve opening pressure range	220 kPa [32 psi] to 250 kPa [36 psi]
Oil filter differential pressure to open bypass	689 kPa [100 psi]

Oil Capacity of Standard Engine (50 Liter Lubricating Oil Pan)

Pan only	50 liters [13.2 U.S. gal] to high
High to low (on dipstick)	15 liters [4.0 U.S. gal]
Lubricating oil filter capacity	2 liters [0.5 U.S. gal]
Total system	53 liters [14.0 U.S. gal] to high

Oil Capacity of Standard Engine (44 Liter Lubricating Oil Pan)

Pan only	44 liters [11.6 U.S. gal] to high
High to low (on dipstick)	9 liters [2.4 U.S. gal]
Lubricating oil filter capacity	2 liters [0.5 U.S. gal]
Total system	49 liters [12.9 U.S. gal] to high

Oil Capacity of Standard Engine (37 Liter Lubricating Oil Pan)

Pan only	37 liters [9.8 U.S. gal] to high
High to low (on dipstick)	10 liters [2.6 U.S. gal]
Lubricating oil filter capacity	2 liters [0.5 U.S. gal]

Total system	42 liters [11.1 U.S. gal] to high
Maximum Oil Temperature	
Maximum oil temperature	135°C [275°F]
The note 50L, 44L, or 37L for the lubricating oil pan capacity can be found on the lubricating oil dipstick.	