

Trainings ▾

Specifications

Wabco™ Air Compressors

This section is for the Wabco™ 912 563 0030 twin-cylinder air compressor.

Cylinders	2
Compressor swept volume @ 1800 ERPM/1.25 MPa	10.6 liters per sec [22.5 cfm]
Piston displacement	318 cc [19.4 C.I.D.]
Bore	157 mm [6.2 in]
Stroke	56 mm [2.2 in]
Speed	1.18 x engine speed
Cooling	Engine coolant
Lubrication	Engine lubricating oil

Plumbing Line Sizes

Coolant inlet and outlet (pipe fitting)	¾-16 UNF
Air inlet (inside diameter)	M27 x 2 depth 14 mm [0.55 in] minimum
Air outlet (minimum inside diameter)	M27 x 2
Unloader port	M10 x 1
Governor mounting (direct)	M10 x 1
Height, overall (approximate)	315 mm [12.4 in]
Width, overall (approximate)	137 mm [5.4 in]
Length, overall (approximate)	358 mm [14.1 in]

Weight (approximate)	22.3 kg [49.2 lb]
----------------------	---------------------

In applications where duty cycles average 10 percent or more or air pressures are above 862 kPa [125 psi], use a discharge line with a minimum inside diameter of 15.9 mm [0.626 in] for single-cylinder compressors and 25.4 mm [1.00 in] for twin-cylinder compressors to prevent carbon buildup. Examples of these applications are as follows: Refuse trucks, pickup and delivery trucks, transit buses, and equipment with high accessory air usage.

Knorr-Bremse™ Air Compressors

This section is for the Knorr K284527 twin-cylinder air compressor.

Cylinders	2
-----------	---

Compressor swept volume @ 2500 ERPM/1.25 MPa	12.5 liters per sec [26.5 cfm]
--	----------------------------------

Piston displacement	630 cc [38.4 C.I.D.]
---------------------	------------------------

Bore	86 mm [3.4 in]
------	------------------

Stroke	54 mm [2.1 in]
--------	------------------

Speed	1.214 x engine speed
-------	----------------------

Cooling	Engine coolant
---------	----------------

Lubrication	Engine lubricating oil
-------------	------------------------

Plumbing Line Sizes

Coolant inlet and outlet (pipe fitting)	¾-16 UNF
---	----------

Air inlet (inside diameter)	M27 x 2
-----------------------------	---------

Air outlet (minimum inside diameter)	M27 x 2
--------------------------------------	---------

Unloader port	M10 x 1
---------------	---------

Height, overall (approximate)	319 mm [12.6 in]
-------------------------------	--------------------

Width, overall (approximate)	160 mm [6.3 in]
------------------------------	-------------------

Length, overall (approximate)	376 mm [14.8 in]
-------------------------------	--------------------

Weight (approximate)	25.2 kg [55.6 lb]
----------------------	---------------------

In applications where duty cycles average 10 percent or more or air pressures are above 862 kPa [125 psi], use a discharge line with a minimum inside diameter of 15.9 mm [0.626 in] for single-cylinder compressors and 25.4 mm [1.00 in] for twin-cylinder compressors to prevent carbon buildup. Examples of these applications are as follows: Refuse trucks, pickup and delivery trucks, transit buses, and equipment with high accessory air usage.

Last Modified: 19-Nov-2024
