

Trainings ▾

Specifications

Fleetguard® filters are manufactured by Cummins Filtration™, which is a subsidiary of Cummins Inc. Fleetguard® filters are developed through joint testing at Cummins Inc. and at Cummins Filtration™. Fleetguard® filters are standard on new Cummins® engines. Cummins Inc. recommends their use.

Fleetguard® products meet all Cummins Inc. Source Approval Test standards to provide the quality filtration necessary to achieve the engine's design life. If other brands are substituted, the purchaser **must** insist on products that the supplier has tested to meet Cummins Inc. high-quality standards.

Cummins Inc. can **not** be responsible for problems caused by non-genuine filters that do **not** meet Cummins Inc. performance or durability requirements.

Cummins Inc. requires a lubricating oil filter be used that meets Cummins Inc. Source Approval Method 10,765.

Filter Types	
Lubricating Oil Filter	
Cummins® Part Number	4331005
Fleetguard® Part Number	LF9080
Pressure-Side Fuel Filter	
Cummins® Part Number	4960198
Fleetguard® Part Number	FF5687
Fuel-Water Separator (Suction-Side Filter)	
Cummins® Part Number	4327370
Fleetguard® Part Number	FS36260
Remote Fuel-Water Separator Filter	
Cummins® Part Number	4095189
Fleetguard® Part Number	FS1006
Coolant Filter	
Fleetguard® Part Number	WF2125 ¹
Fleetguard® Part Number	WF2126 ² (Cummins® Part Number 4907485)
Fleetguard® Part Number	WF2127 ³

Filter Types

Air / Oil Separator Filter

Fleetguard® Part Number

AS2474

1. This filter is designed for use with Cummins Filtration™ extended service cooling systems, which extends cooling system service to 1 year, 80,467 km [150,000 miles], or 4000 hours, whichever comes first. This filter is used for cooling systems up to 76 liters [20 U.S. gallons]. Refer to Cummins® Coolant Requirements and Maintenance, Bulletin 3666132. Fleetguard® ES coolant **must** be used for all fill and top-off, which is critical for extended cooling system maintenance intervals.
2. This filter is designed for extended service intervals up to 80,467 km [50,000 miles] when using TMC RP329 or RP330 coolants and is used for cooling systems up to 76 liters [20 U.S. gallons]. Refer to Cummins® Coolant Requirements and Maintenance, Bulletin 3666132.
3. This filter has been designed for extended service intervals of 80,467 to 241,402 km [50,000 to 150,000 miles]. It has no chemical additives and can be used in the following systems:
 - Cooling systems above 76 liters [20 U.S. gallons] in capacity.
 - See maintenance chart below.

Cooling System Capacity	80,467 km [50,000 Mile] Service Interval with RP329/330 Coolant or Treated Water (Fleetcool™ or DCA4)	241,402 km [150,000 Mile] Service Interval with ES Coolant (ES Liquid)
0 to 76 liters [0 to 20 U.S. gallons]	0.95 liters [1 U.S. qt] (10 units)	0.95 liters [1 U.S. qt] (15 units)
76 to 151 liters [20 to 40 U.S. gallons]	1.89 liters [2 U.S. qt] (20 units)	1.89 liters [2 U.S. qt] (30 units)
151 to 227 liters [40 to 60 U.S. gallons]	2.84 liters [3 U.S. qt] (30 units)	2.84 liters [3 U.S. qt] (45 units)
227 to 303 liters [60 to 80 U.S. gallons]	3.79 liters [4 U.S. qt] (40 units)	3.79 liters [4 U.S. qt] (60 units)
303 to 379 liters [80 to 100 U.S. gallons]	4.73 liters [5 U.S. qt] (50 units)	4.73 liters [5 U.S. qt] (75 units)

Note : Filters must meet Cummins Inc. SAM 10,769. Fleetguard® filters meet Cummins Inc. SAM 10,769. The standard filter for the engine is Fleetguard® WF2126. For systems larger than 379 liters [100 U.S. gallons], use 0.94 liters [1 U.S. quart] per 57 liters [15 U.S. gallons]. Consult the vehicle manufacturer for total cooling system capacity.

