

Trainings ▾

Specifications

Industrial Applications

Coolant Capacity	9.5 liters [2.5 gal]
------------------	----------------------

Standard Modulating Thermostat Range	82 to 93°C [180 to 200°F]
--------------------------------------	---------------------------

Cylinder Block Coolant Pressure (pressure cap removed):

Minimum:

Closed Thermostat (1800 rpm no load)	138 kPa [20 psi]
--------------------------------------	------------------

Cylinder Block Coolant Pressure (pressure cap removed):

Maximum:

Closed Thermostat	275 kPa [40 psi]
-------------------	------------------

Maximum Allowable Operating Coolant Temperature	100°C [212°F]
---	---------------

Minimum Recommended Operating Coolant Temperature	70°C [160°F]
---	--------------

Maximum Allowable Deaeration Time	35 minutes
-----------------------------------	------------

Minimum Recommended Pressure Cap	48 kPa [7 psi]
----------------------------------	----------------

Generator Set Applications

Coolant Capacity:	9.5 liters [2.5 gal]
-------------------	----------------------

Standard Modulating Thermostat Range	82 to 93°C [180 to 200°F]
--------------------------------------	---------------------------

Minimum Pressure Cap	48 kPa [7 psi]
----------------------	----------------

Maximum Coolant Friction Head External to Engine

1500 rpm	55 kPa [8 psi]
----------	----------------

1800 rpm	69 kPa [10 psi]
----------	-----------------

Maximum Static Head of Coolant Above Engine Crank Centerline	14 m [46 ft]
Maximum Top Tank Temperature for Standby/Prime Power	104/100°C [220/212°F]

Last Modified: 01-May-2012
