

Trainings ▾

Specifications

Maintain the following limits during the engine test/run-in procedures:

Due to variations in ratings of different engine models, refer to the specific Engine Data Sheet for the particular engine model being tested.

Charge Air Cooler Restriction (maximum):

Mercury	89 mm Hg [3.5 in Hg]
Pounds Force	12 kPa [1.7 psi]

Intake Restriction (maximum at advertised horsepower):

Clean Air Filter	254 mm H ₂ O [10.0 in H ₂ O]
Dirty Air Filter	635 mm H ₂ O [25.0 in H ₂ O]
Maximum Exhaust Back Pressure	75 mm Hg [3.0 in Hg]

Oil Pressure:

Low idle (minimum allowable)	69 kPa [10.0 psi]
At 1200 rpm or Torque Peak (minimum allowable)	207 kPa [30 psi]
At Advertised rpm	276 to 345 kPa [40 to 50 psi]
Maximum Cylinder Block Coolant Pressure (closed thermostat)	372 kPa [54 psi]
Maximum Allowable Operating Temperature	100°C [212°F]
Maximum Allowable Fuel Inlet Temperature	71°C [160°F]

Fuel Inlet Maximum Restriction:

Clean Fuel Filter	152 mm Hg [6.0 in Hg]
Dirty Fuel Filter	254 mm Hg [10.0 in Hg]

Blowby (maximum at advertised horsepower):

New or Rebuilt Engines (maximum) (less than 160,000 km [100,000 mi] or 3600 hours)	305 mm H ₂ O [12 in H ₂ O]
Used Engines (maximum) (over 160,000 km [100,000 mi] or 3600 hours)	460 mm H ₂ O [18 in H ₂ O]

Last Modified: 27-Feb-2020
