

Trainings ▾

Specifications

Horsepower

B3.9, B5.9	Refer to engine dataplate
------------	---------------------------

Bore

B3.9, B5.9	102 mm [4.02 in]
------------	------------------

Stroke

B3.9, B5.9	120 mm [4.72 in]
------------	------------------

Displacement

B3.9	3.9 liters [238 C.I.D.]
------	-------------------------

B5.9	5.9 liters [360 C.I.D.]
------	-------------------------

Engine Weight (dry) Less Flywheel and Electric Components

B3.9	308 to 329 kg [679 to 725 lb]
------	-------------------------------

B5.9	388 to 411 kg [855 to 906 lb]
------	-------------------------------

Firing Order

B3.9	1-3-4-2
------	---------

B5.9	1-5-3-6-2-4
------	-------------

Valve Clearance

B3.9 and B5.9

Intake	0.25 mm [0.010 in]
--------	--------------------

Exhaust	0.51 mm [0.020 in]
---------	--------------------

Compression Ratio

B3.9	(rotary pump) 17.6:1
------	----------------------

B5.9	(in-line pump) 17.9:1
------	-----------------------

Crankshaft Rotation (viewed from the front of the engine)

B3.9 and B5.9	Clockwise
Aspiration Turbocharged	
B3.9	Yes
B5.9	Yes
Aspiration Charge Air Cooled	
B3.9	Yes
B5.9	Yes