

Trainings ▾

Specifications

Automotive Applications

Maximum Allowable Intake Restriction

Clean Air Filter Element 254 mm H₂O [10 in H₂O] Dirty Air Filter Element 635 mm H₂O [25 in H₂O]

Refer to the following table for the control parts list (CPL), engine model, engine horsepower rating, and corresponding rated turbocharger boost pressure.

Note : Measurement of boost pressure is not a shortcut to logical troubleshooting. Low power can be caused by the fuel used, filter maintenance, and several engine components. Follow the troubleshooting charts for Engine Power Output Low, and measure boost pressure as indicated. Refer to this section, General Information, for measurement instructions.

These pressures are valid **only** at rated conditions (rated speed and power). Any attempt to use the values at engine speeds and loads other than those specified will result in an incorrect diagnosis.

B Series Engines' Turbocharger Boost Pressure Specifications

CPL	MODE L ENGIN E	hp @ rpm RATING	PEAK TORQ UE ft- lb @ rpm	RATED BOOST (in Hg)			PEAK TORQUE BOOST (in Hg)		
				min	nom	max	min	nom	max
591	4B3.9	64 @ 2200	N/A	N/A	N/A	N/A	N/A	N/A	N/A
591	4B3.9	64 @ 2200	N/A	N/A	N/A	N/A	N/A	N/A	N/A
592	4BTA3 .9	70 @ 2100	N/A	11	14	17	N/A	N/A	N/A
592	4BTA3 .9	71 @ 2200	N/A	12	15	18	N/A	N/A	N/A
592	4BTA3 .9	80 @ 2200	N/A	14	17	20	N/A	N/A	N/A
592	4BTA3 .9	92 @ 2100	N/A	16	19	22	N/A	N/A	N/A

592	4BTA3 .9	93 @ 2200	N/A	18	21	24	N/A	N/A	N/A
592	4BTA3 .9	94 @ 2200	N/A	18	21	24	N/A	N/A	N/A
592	4BTA3 .9	96 @ 2300	N/A	19	22	25	N/A	N/A	N/A
592	4BTA3 .9	100 @ 2500	N/A	22	25	28	N/A	N/A	N/A
594	4BTA3 .9	95 @ 2200	N/A	15	18	21	N/A	N/A	N/A
594	4BTA3 .9	112 @ 2300	N/A	21	24	27	N/A	N/A	N/A
594	4BTA3 .9	125 @ 2200	N/A	25	28	31	N/A	N/A	N/A
646	4BT3. 9	71 @ 1500	N/A	9	12	15	N/A	N/A	N/A
646	4BT3. 9	82 @ 1800	N/A	11	14	17	N/A	N/A	N/A
710	4BT3. 9	75 @ 2200	N/A	13	16	19	N/A	N/A	N/A
710	4BT3. 9	100 @ 2500	N/A	22	25	28	N/A	N/A	N/A
711	4BT3. 9	71 @ 1500	N/A	9	12	15	N/A	N/A	N/A
711	4BT3. 9	82 @ 1800	N/A	11	14	17	N/A	N/A	N/A
721	4B3.9	80 @ 2800	N/A	N/A	N/A	N/A	N/A	N/A	N/A
730	4BT3. 9	85 @ 2500	235 @ 1200	17	20	23	9	10	11
730	4BT3. 9	91 @ 2200	259 @ 1400	17	20	23	11	12	13
741	4BT3. 9	130 @ 2500	N/A	18	21	24	N/A	N/A	N/A
741	4BT3. 9	150 @ 2800	N/A	25	28	31	N/A	N/A	N/A
741	4BT3. 9	150 @ 2800	N/A	25	28	31	N/A	N/A	N/A
762	4BT3. 9	105 @ 2500	N/A	28	32	36	N/A	N/A	N/A

762	4BT3. 9	105 @ 2800	N/A	31	35	39	N/A	N/A	N/A
763	4BT3. 9	67 @ 2200	N/A	10	14	16	N/A	N/A	N/A
763	4BT3. 9	71 @ 2200	N/A	10	14	16	N/A	N/A	N/A
767	4BT3. 9	105 @ 2500	N/A	24	28	31	N/A	N/A	N/A
767	4BT3. 9	105 @ 2800	N/A	27	30	33	N/A	N/A	N/A
826	4BT3. 9	87 @ 1500	N/A	15	18	21	N/A	N/A	N/A
857	4BT3. 9	120 @ 2500	N/A	40	44	48	N/A	N/A	N/A
858	4BT3. 9	105 @ 2500	N/A	35	39	43	N/A	N/A	N/A
937	4BT3. 9	74 @ 1500	N/A	10	13	16	N/A	N/A	N/A
971	4BT3. 9	96 @ 2200	N/A	19	22	25	N/A	N/A	N/A
971	4BT3. 9	100 @ 2500	N/A	22	25	28	N/A	N/A	N/A
986	4BTA3 .9	120 @ 2500	N/A	28	31.0	34	17	19.4	21
1201	4BT3. 9	80 @ 2500	N/A	19	22	25	N/A	N/A	N/A
1202	4BT3. 9	74 @ 2500	N/A	18	21	24	N/A	N/A	N/A
1260	4BTA3 .9	105 @ 2500	N/A	22	24.5	27	14	15.6	17
1268	4BT3. 9	105 @ 2500	N/A	28	32	36	N/A	N/A	N/A
1520	4BTG2	104 @ 1800	N/A	19	21	23	N/A	N/A	N/A
1521	4BT3. 9	74 @ 1500	N/A	3.4	6.4	9.4	N/A	N/A	N/A
1521	4BT3. 9	86 @ 1800	N/A	5.8	8.8	12.0	N/A	N/A	N/A
1521	4BT3. 9	88 @ 1800	N/A	19	21	23	N/A	N/A	N/A

1525	4BT3. 9	72 @ 1500	N/A	N/A	N/A	N/A	N/A	N/A	N/A
1525	4BTG2	87 @ 1500	N/A	12	13	14	N/A	N/A	N/A
1963	4BTA3 .9	116 @ 2500	295 @ 1500	36	39.3	42	23	25.6	29
1963	4BTA3 .9	116 @ 2500	299 @ 1500	37	39.9	43	23	26	29
1963	4BTA3 .9	125 @ 2200	350 @ 1500	37	40	43	29	32	35
1963	4BTA3 .9	130 @ 2500	344 @ 1500	36	39	42	27	30	33
1965	4BT3. 9	80 @ 2200	229 @ 1500	39	42	45	17	20	23
1965	4BT3. 9	85 @ 2200	242 @ 1500	43	46	49	19	22	25
1965	4BTA3 .9	85 @ 2200	254 @ 1500	43	46	49	19`	22	25
1965	4BT3. 9	90 @ 2200	269 @ 1500	45	49	53	22	26	30
1965	4BT3. 9	92 @ 2100	293 @ 1500	46	49.3	52	28	31	34
1965	4BT3. 9	92 @ 2100	295 @ 2100	45	49	53	25	29	33
1966	4BT3. 9	92 @ 2000	302 @ 1300	31	33.7	37	20	22.7	26
1967	4BT3. 9	85 @ 2500	239 @ 1500	38	41.5	45	16	20	24
1967	4BT3. 9	90 @ 2500	254 @ 1500	38	42	45	20	24	28
1967	4BT3. 9	95 @ 2200	285 @ 1500	38	42.2	45	24	27.9	32
1967	4BT3. 9	100 @ 2200	298 @ 1500	41	44	47	27	30	33
1967	4BT3. 9	105 @ 2100	293 @ 1500	39	42.3	45	26	29.2	32
1967	4BT3. 9	105 @ 2400	280 @ 1500	41	44.3	47	23	26.6	31
1967	4BT3. 9	110 @ 2500	293 @ 1500	42	44.8	48	25	29	33

2021	4BT3. 9	93 @ 2200	353 @ 1550	N/A	N/A	N/A	N/A	N/A	N/A
2109	4BTA3 .9	107 @ 2100	327 @ 1500	40	42.7	46	30	32.5	36
2109	4BTA3 .9	107 @ 2100	334 @ 1500	39	42	45	30	33	36
2109	4BTA3 .9	107 @ 2100	328 @ 1600	40	42.7	46	30	32.5	36
2109	4BTA3 .9	110 @ 2200	328 @ 1500	39	42	45	30	33	36
2109	4BTA3 .9	110 @ 2200	328 @ 1500	39	42.0	45	30	33	36
2109	4BTA3 .9	110 @ 2200	333 @ 1500	39	41.7	45	30	33.3	36
2109	4BTA3 .9	116 @ 2500	300 @ 1500	39	42	45	29	32	35
2109	4BTA3 .9	116 @ 2500	312 @ 1500	40	43	46	29	32	35
2264	4BTA3 .9	125 @ 2200	355 @ 1500	36	39	42	29	32	35
2302	4BT3. 9	110 @ 2500	278 @ 1500	41	43.7	47	24	26.6	30
2302	4BT3. 9	110 @ 2500	278 @ 1500	40	43	46	23	26	29
2302	4BT3. 9	110 @ 2500	293 @ 1500	41	43.7	47	26	28.6	32
2351	4BTA3 .9	110 @ 2200	328 @ 1500	37	39.9	43	27	29.5	33
2359	4BT3. 9	85 @ 2500	239 @ 1500	39	41.5	45	17	20	23
2361	4B3.9	74 @ 2500	201 @ 1200	N/A	N/A	N/A	N/A	N/A	N/A
2361	4B3.9	80 @ 2500	201 @ 1200	N/A	N/A	N/A	N/A	N/A	N/A
2361	4B3.9	80 @ 2500	201 @ 1200	N/A	N/A	N/A	N/A	N/A	N/A
2374	4B3.9	75 @ 2200	201 @ 1200	N/A	N/A	N/A	N/A	N/A	N/A
2478	4BT3. 9	80 @ 2200	229 @ 1500	39	41.8	45	17	20	23

2486	4B3.9	75 @ 2200	201 @ 1200	N/A	N/A	N/A	N/A	N/A	N/A
2488	4B3.9	54 @ 2000	179 @ 1200	N/A	N/A	N/A	N/A	N/A	N/A
2489	4B3.9	60 @ 2200	179 @ 1200	N/A	N/A	N/A	N/A	N/A	N/A
2490	4B3.9	67 @ 2200	192 @ 1200	N/A	N/A	N/A	N/A	N/A	N/A
2599	4B3.9	75 @ 2200	193 @ 1200	N/A	N/A	N/A	N/A	N/A	N/A
2599	4B3.9	80 @ 2500	193 @ 1200	N/A	N/A	N/A	N/A	N/A	N/A
2601	4B3.9	60 @ 2000	180 @ 1200	N/A	N/A	N/A	N/A	N/A	N/A
2601	4 B3.9	60 @ 2000	190 @ 1200	N/A	N/A	N/A	N/A	N/A	N/A
2808	4BT3. 9	110 @ 2500	293 @ 1500	41	43.7	47	24	26.6	30
596	6B5.9	93 @ 2200	262 @ 1100	N/A	N/A	N/A	N/A	N/A	N/A
598	6BT5. 9	160 @ 2500	N/A	28	32	36	N/A	N/A	N/A
598	6BT5. 9	160 @ 2800	N/A	31	35	39	N/A	N/A	N/A
600	6BTA5 .9	180 @ 2500	N/A	39	43	47	N/A	N/A	N/A
692	6BT5. 9	160 @ 2500	N/A	30	34	38	N/A	N/A	N/A
692	6BT5. 9	160 @ 2600	N/A	31	35	39	N/A	N/A	N/A
697	6BT5. 9	113 @ 1500	N/A	15	19	21	N/A	N/A	N/A
697	6BT5. 9	134 @ 1800	N/A	21	24	27	N/A	N/A	N/A
713	6BT5. 9	113 @ 1500	N/A	12	18	21	N/A	N/A	N/A
713	6BT5. 9	134 @ 1800	N/A	21	24	27	N/A	N/A	N/A
715	6BTA5 .9	143 @ 2100	N/A	26	29	32	N/A	N/A	N/A

716	6BT5. 9	156 @ 2500	N/A	45	49	53	N/A	N/A	N/A
728	6BT5. 9	128 @ 2800	N/A	19	22	25	N/A	N/A	N/A
728	6BT5. 9	130 @ 2650	N/A	19	22	25	N/A	N/A	N/A
729	6BT5. 9	134 @ 2200	N/A	23	26	29	N/A	N/A	N/A
742	6BT5. 9	152 @ 2500	N/A	30	33	36	N/A	N/A	N/A
742	6BT5. 9	180 @ 2500	N/A	39	43	47	N/A	N/A	N/A
742	6BT5. 9	210 @ 2600	N/A	47	51	55	N/A	N/A	N/A
766	6BT5. 9	160 @ 2500	N/A	28	32	36	N/A	N/A	N/A
766	6BT5. 9	160 @ 2800	N/A	31	35	39	N/A	N/A	N/A
791	6B5.9	120 @ 2800	N/A	N/A	N/A	N/A	N/A	N/A	N/A
791	6B5.9	120 @ 2800	N/A	N/A	N/A	N/A	N/A	N/A	N/A
804	6BT5. 9	145 @ 2600	N/A	39	43	47	N/A	N/A	N/A
804	6BT5. 9	160 @ 2500	N/A	38	41	44	N/A	N/A	N/A
807	6BT5. 9	99 @ 2200	N/A	13	16	19	N/A	N/A	N/A
834	6BTA5 .9	180 @ 2500	N/A	32	36	40	N/A	N/A	N/A
856	6BTA5 .9	180 @ 2500	N/A	46	50	54	N/A	N/A	N/A
912	6BTA5 .9	190 @ 2600	N/A	34	38	42	N/A	N/A	N/A
938	6BT5. 9	135 @ 2200	442 @ 1400	23	25	28	19	21	23
938	6BT5. 9	137 @ 2200	393 @ 1600	18	21	24	16	18	20
938	6BT5. 9	140 @ 2200	426 @ 1300	24	27	30	15	17	19

938	6BT5. 9	145 @ 2200	425 @ 1500	25	28	31	19	21	23
938	6BT5. 9	87 @ 2200	265 @ 1200	10	13	16	5	6	7
938	6BT5. 9	97 @ 2200	270 @ 1200	13	16	19	6	7	8
943	6BT5. 9	120 @ 2100	N/A	18	21	24	N/A	N/A	N/A
947	6BT5. 9	145 @ 2600	N/A	24	27	30	N/A	N/A	N/A
947	6BT5. 9	160 @ 2500	N/A	29	33	37	N/A	N/A	N/A
947	6BT5. 9	160 @ 2600	N/A	31	35	39	N/A	N/A	N/A
947	6BT5. 9	130 @ 2500	N/A	20	23	26	N/A	N/A	N/A
948	6BT5. 9	145 @ 2600	N/A	24	27	30	N/A	N/A	N/A
949	6BT5. 9	88 @ 2000	N/A	10	13	16	N/A	N/A	N/A
949	6BT5. 9	121 @ 2200	N/A	14	17	20	N/A	N/A	N/A
949	6BT5. 9	124 @ 2400	N/A	21	24	27	N/A	N/A	N/A
949	6BT5. 9	126 @ 2100	N/A	19	22	25	N/A	N/A	N/A
949	6BT5. 9	130 @ 2500	N/A	23	26	29	N/A	N/A	N/A
949	6BT5. 9	140 @ 2200	N/A	24	27	30	N/A	N/A	N/A
949	6BT5. 9	142 @ 2100	N/A	24	24	30	N/A	N/A	N/A
949	6BT5. 9	145 @ 2200	N/A	25	28	31	N/A	N/A	N/A
949	6BT5. 9	148 @ 2300	N/A	27	30	33	N/A	N/A	N/A
949	6BT5. 9	152 @ 2500	N/A	28	32	36	N/A	N/A	N/A
950	6BT5. 9	120 @ 2100	N/A	18	21	24	N/A	N/A	N/A

953	6BTA5 .9	220 @ 2500	N/A	23	26	29	N/A	N/A	N/A
953	6BTA5 .9	250 @ 2600	N/A	44	48	52	N/A	N/A	N/A
961	6BT5. 9	115 @ 1500	N/A	16	19	22	N/A	N/A	N/A
961	6BT5. 9	135 @ 1800	N/A	22	25	28	N/A	N/A	N/A
970	6BTA- M2	250 @ 2600	N/A	32	36	40	N/A	N/A	N/A
970	6BTA- M2	300 @ 2800	N/A	46	50	54	N/A	N/A	N/A
970	6BTS WA	300 @ 2800	N/A	40	44	48	N/A	N/A	N/A
983	6BTA5 .9	157 @ 2500	N/A	35	39	43	N/A	N/A	N/A
983	6BTA5 .9	177 @ 2500	N/A	38	42	46	N/A	N/A	N/A
998	6BTA5 .9	200 @ 2500	N/A	45	49	53	N/A	N/A	N/A
1160	6BT5. 9	160 @ 2500	N/A	29	33	37	N/A	N/A	N/A
1165	6BTA5 .9	227 @ 1760	N/A	37	41	45	N/A	N/A	N/A
1165	6BTA5 .9	255 @ 2100	N/A	46	50	54	N/A	N/A	N/A
1168	6BT5. 9	148 @ 2300	N/A	25	28	31	N/A	N/A	N/A
1168	6BT5. 9	152 @ 2500	N/A	27	31	35	N/A	N/A	N/A
1209	6BTA5 .9	176 @ 2300	N/A	30	33	36	N/A	N/A	N/A
1266	6BT5. 9	142 @ 2500	N/A	27	31	35	N/A	N/A	N/A
1279	6BT5. 9	125 @ 2200	412 @ 1400	18	20	22	14	16	18
1322	6BTA- M1	220 @ 2500	N/A	32	36	40	N/A	N/A	N/A
1322	6BTA5 .9	250 @ 2600	N/A	34	38	42	N/A	N/A	N/A

1322	6BTA-M1	250 @ 2600	N/A	42	46	50	N/A	N/A	N/A
1419	6BT5.9	250 @ 2500	N/A	38	42	46	N/A	N/A	N/A
1518	6BT5.9	169 @ 1800	N/A	32	35	39	N/A	N/A	N/A
1549	6BTA5.9	160 @ 2500	400 @ 1600	30	34	38	23	25	28
1552	6BTA5.9	210 @ 2500	485 @ 1600	44	47.7	52	29	31.9	35
1570	6BTJWA	250 @ 2600	N/A	35	39	43	N/A	N/A	N/A
1579	6BTA5.9	160 @ 2500	400 @ 1600	31	35.4	39	14	17.2	20
1613	6BTSWA	250 @ 2600	N/A	36	40	44	N/A	N/A	N/A
1640	6BTA5.9	185 @ 2200	531 @ 1500	41	45	50	27	30	33
1863	6BTA A	180 @ 2500	42- @ 1500	36	39	42	22	25	28
1889	6BTA5.9	185 @ 2400	550 @ 1500	43	46	49	30	33	36
1889	6BTA5.9	200 @ 2500	550 @ 1500	48	51	54	30	33	36
1914	6BTA5.9	190 @ 2300	475 @ 1600	44	48	52	22	26	30
1945	6BT5.9	200 @ 2200	583 @ 1500	41	46	51	31	34	37
1945	6BTA5.9	200 @ 2500	581 @ 1500	41	46	51	30	33	36
1948	6BT5.9	148 @ 2200	440 @ 1600	38	41	44	25	28	31
1948	6BT5.9	148 @ 2200	440 @ 1600	37	40	43	43	24	37
1948	6BT5.9	152 @ 2500	414 @ 1600	40	43	46	24	27	30
1948	6BT5.9	155 @ 2100	449 @ 1600	39	41.8	45	24	27	30
1959	6BTA5.9	160 @ 2500	400 @ 1600	30	34	38	18	21	24

1962	6BTA5 .9	147 @ 2000	428 @ 1500	33	36	39	21	24	27
1962	6BTA5 .9	150 @ 2200	466 @ 1500	35	38	41	23	26	29
1962	6BTA5 .9	150 @ 2200	466 @ 1500	35	38	41	23	26	29
1962	6BTA5 .9	150 @ 2200	483 @ 1500	35	38.4	41	26	28.6	32
1962	6BTA5 .9	160 @ 2000	462 @ 1500	38	41	44	23	26	29
1962	6BTA5 .9	166 @ 2075	474 @ 1500	42	44.6	48	25	28.1	31
1962	6BTA5 .9	167 @ 2000	480 @ 1500	36	39	42	24	27	30
1962	6BTA5 .9	150 @ 2200	483 @ 1500	35	38	41	26	29	32
1962	6BTA5 .9	153 @ 2200	485 @ 1500	37	40	43	24	27	30
1962	6BTA5 .9	165 @ 2200	512 @ 1500	42	45	48	28	31	34
1962	6BTA5 .9	165 @ 2200	532 @ 1500	42	44.6	48	29	31.6	35
1962	6BTA5 .9	168 @ 2200	541 @ 1500	37	40	43	24	27	30
1962	6BTA5 .9	167 @ 2000	479 @ 1500	40	43	46	25	28	31
1962	6BTA5 .9	170 @ 2300	475 @ 1500	42	45	48	23	26	29
1962	6BTA5 .9	169 @ 2100	480 @ 1500	41	44	47	25	28	31
1962	6BTA5 .9	169 @ 2100	480 @ 1500	41	44	47	25	28	31
1968	6BTA A	160 @ 2500	400 @ 1600	30	34	38	19	22	25
1975	6BTA5 .9	330 @ 2800	687 @ 2000	52	57	62	37	41	45
1989	6BTA5 .9	185 @ 2500	553 @ 1500	47	51	55	33	37	41
2016	6BTA A5.9	129 @ 2500	347 @ 1500	25	29.2	33	11	13.9	17

2017	6BTA5 .9	178 @ 2500	474 @ 1500	34	36.6	40	19	21.6	25
2023	6BTA A	21 @ 2600	440 @ 1600	48	51	54	23	26	29
2035	6BTA5 .9	195 @ 2800	420 @ 1600	32	35	38	25	28.5	31
2063	6BTA5 .9	185 @ 2300	580 @ 1500	40	43	46	33	36	39
2063	6BTA5 .9	185 @ 2400	558 @ 1500	46	48.7	52	30	33.1	36
2063	6BTA5 .9	185 @ 2200	566 @ 1500	40	43	46	33	36	39
2063	6BTA5 .9	174 @ 2200	590 @ 1500	45	48	51	36	39	42
2071	6BT5. 9	97 @ 2200	267 @ 1700	21	24	27	13	16	19
2071	6BT5. 9	97 @ 2200	270 @ 1700	20	24	28	12	16	20
2071	6BT5. 9	101 @ 2200	313 @ 1500	23	26	29	11	14	17
2071	6BT5. 9	118 @ 2400	327 @ 1600	35	38	41	16	19	22
2071	6BT5. 9	110 @ 1900	341 @ 1600	27	30	33	17	20	23
2071	6BT5. 9	110 @ 2200	341 @ 1600	28	31	34	18	21	24
2071	6BT5. 9	120 @ 2200	372 @ 1500	32	35	38	22	25	28
2071	6BT5. 9	126 @ 2100	380 @ 1600	29	32	35	19	22	25
2071	6BT5. 9	130 @ 2200	388 @ 1600	33	36	39	20	23	26
2071	6BT5. 9	130 @ 2500	368 @ 1600	42	44.9	48	18	21	24
2071	6BT5. 9	135 @ 2100	404 @ 1600	30	33	36	19	22	25
2071	6BT5. 9	135 @ 2200	419 @ 1500	32	35	38	19	22	25
2071	6BT5. 9	135 @ 2200	419 @ 1600	35	38	41	23	26	29

2071	6BT5. 9	135 @ 2400	379 @ 1600	42	45	48	21	24	27
2071	6BT5. 9	135 @ 2200	419 @ 1600	37	40	43	25	28	31
2071	6BT5. 9	135 @ 2100	419 @ 1500	30	33	36	19	22	25
2071	6BT5. 9	140 @ 2000	416 @ 1600	32	35	38	23	26	29
2071	6BT5. 9	145 @ 2100	438 @ 1500	38.4	41.4	44.4	40	42.1	44
2071	6BT5. 9	137 @ 2000	440 @ 1600	32	35.1	38	28	31	34
2072	6BTA5 .9	174 @ 2500	458 @ 1500	43	46.1	49	24	27.2	30
2072	6BTA5 .9	174 @ 2500	470 @ 1500	42	45	48	24	27	30
2174	6BTA A5.9	180 @ 2500	420 @ 1500	36	39	42	22	25	28
2175	6BTA A5.9	215 @ 2600	440 @ 1600	48	51	54	23	26	29
2122	6BTA5 .9	177 @ 2500	480 @ 1500	N/A	N/A	N/A	N/A	N/A	N/A
2208	6BTA	370 @ 3000	726 @ 2200	56	59	62	40	43	46
2249	6BTA A5.9	232 @ 2500	590 @ 1500	50	52.6	56	30	32.5	36
2292	6BTA5 .9	147 @ 2000	438 @ 1500	35	38	41	23	26	29
2292	6BTA5 .9	160 @ 1900	479 @ 1500	38	41	44	23	26	29
2292	6BTA5 .9	169 @ 2100	480 @ 1500	41	44	47	25	28	31
2292	6BTA5 .9	169 @ 2100	485 @ 1500	41	44	47	23	26	29
2292	6BTA5 .9	169 @ 2100	485 @ 1500	45	47.5	51	29	31.6	35
2292	6BTA5 .9	167 @ 2000	480 @ 1500	37	39.6	43	25	27.5	31
2308	6BTA A5.9	180 @ 2500	420 @ 1500	36	39	42	22	25	28

2479	6BTA5.9	174 @ 2200	590 @ 1500	46	48.4	51	37	39.9	43
2530	6BT5.9	135 @ 1800	N/A	30	32.5	35	N/A	N/A	N/A
2530	6BT5.9	143 @ 1800	N/A	29	31.9	35	N/A	N/A	N/A
2530	6BT5.9	170 @ 1800	N/A	20	21.8	23	N/A	N/A	N/A

Industrial Applications

Maximum Intake Restriction

Clean Air Filter Element 254 mm H₂O [10 in H₂O] Dirty Air Filter Element 635 mm H₂O [25.0 in H₂O]

Recommended Intake Piping Size (inner diameter)

B3.9, B4.5 and B4.5 RGT 76 mm [3 in] B5.9 101.6 mm [4 in]