

Trainings ▾

Specifications

Minimum Recommended Battery Capacity @ -18°C [0°F]

12-VDC Starter
With Light Accessories(1)
B3.9 625 CCAB5.9 800 CCA

12-VDC Starter
With Heavy Accessories(2)
B3.9 800 CCAB5.9 950 CCA

24-VDC Starter
With Light Accessories(1)
B3.9 400 CCAB5.9 400 CCA

24-VDC Starter
With Heavy Accessories(2)
B3.9 400 CCAB5.9 475 CCA

Maximum Allowable Starting Circuit Resistance
12-VDC Starter
B3.9 0.0012 ohmsB5.9 0.0012 ohms

Maximum Allowable Starting Circuit Resistance
24-VDC Starter
B3.9 0.0020 ohmsB5.9 0.0020 ohms

- 1. Typical light accessories include alternator, small steering pump, and disengaged clutch.
- 2. Typical heavy accessories include hydraulic pump and torque converter.

Batteries (Specific Gravity)	
Specific Gravity at 27° C [80° F]	State of Charge
1.260 to 1.280	100%
1.230 to 1.250	75%
1.200 to 1.220	50%
1.170 to 1.190	25%
1.110 to 1.130	Discharged

Last Modified: 02-Jul-2007
