

Trainings ▾

General Information

WARNING

Do not mix gasoline or alcohol with diesel fuel. These mixtures can cause explosions.

CAUTION

Due to the precise tolerances of diesel injection systems, it is extremely important that the fuel be kept clean and free of dirt or water. Dirt or water in the system can cause severe damage to both the fuel pump and the injectors.

Cummins Inc. recommends the use of ASTM number 2 D fuel. The use of number 2 diesel fuel will result in optimum engine performance.

At operating temperatures below 0°C [32°F], acceptable performance can be obtained by using blends of number 2 D and number 1 D.

Note : Lighter fuels can reduce fuel economy.

The viscosity of the fuel **must** be kept above 1.3 cSt at 40°C [104°F] to provide adequate fuel system lubrication.

The following chart lists acceptable alternate fuels for QSK23 engines.

Acceptable Substitute Fuels - Cummins Fuel System

No. 1D Diesel	No. 2D Diesel	No. 1K Kerosene	Jet-A	Jet-A1	JP-5	JP-8	Jet-B	JP-4	CITE
1	OK	1	1	1	OK	OK	NOT OK	NOT OK	NOT OK

OK - **ONLY** if fuel lubricity is adequate. Refer to Fuel for Cummins Engines, Bulletin 3379001 (/qs3/pubsys2/xml/en/bulletin/3379001.html). Acceptable **ONLY** if chrome plated injector plated injector plungers fuel additive AND the heavy duty carbon graphite bushed gear pump are used, or the fuel is blended with enough fuel additive to increase the lubricity above the minimum level. Refer to Fuel for Cummins Engines, Bulletin 3379001 (/qs3/pubsys2/xml/en/bulletin/3379001.html).

Note: Any adjustment to compensate for reduced performance with a fuel system using substitute fuel is **not** warrantable.

Additional information for fuel recommendations and specifications can be found in Fuel for Cummins Engines, Bulletin 3379001 (</qs3/pubsys2/xml/en/bulletin/3379001.html>). See ordering information in the Section L.

Last Modified: 06-Jan-2003
