

Trainings ▾

General Information

Component	Wrench Size	Torque Value	
		N•m	ft-lb
Oil pan drain plug	32 mm	68	50
Crosshead adjusting screw locknut (with / without adapter)	17 mm	60/65	44/48
Rocker cover capscrews	12 mm	10	89 in-lb
Injector adjusting screw locknut	27 mm	225	165
Injector adjusting screw	13 mm	32	24
Valve adjusting screw locknut (with / without adapter)	19 mm	48/68	35/50
Turbocharger oil drain line capscrews	14 mm	66	49
Turbocharger oil supply line fitting (Industrial) (turbocharger side)	12 mm	31	23
Turbocharger oil supply line fitting (Power Generation) (turbocharger side)	12 mm	29	22
Turbocharger oil supply line fitting (cylinder block side)	19 mm	29	22
Cooling fan automatic belt tensioner (Industrial)	19 mm	113	83

Component	Wrench Size	Torque Value	
		N•m	ft-lb
Cooling fan belt tensioner (Power Generation) (3 clamping bolts)	14 mm	66	49
Cooling fan belt tensioner (Power Generation) (mounting bolt)	19 mm	113	83
Cooling fan belt tensioner (Power Generation) locknut	19 mm	196	125
Alternator adjusting link mounting capscrew	19 mm	75	55
Alternator belt adjustment locknuts	22 mm	196	125
Crankcase breather mounting capscrews	17 mm	66	48

Last Modified: 06-Jan-2003
