



# Technical Service Bulletin

Technical Service Bulletin: tsb101282

Released Date: 28-Aug-2003

Main Bearing Inspect for Reuse Guidelines and Repair

## Main Bearing Inspect for Reuse Guidelines and Repair

### Warranty Statement

The information in this document has no effect on present warranty coverage or repair practices, nor does it authorize TRP or Campaign actions.

### Contents

This service/parts topic obsoletes 00T1-4A. Replace 00T1-4A with this topic.

This service/parts topic provides information to assist all repair and service personnel in diagnosing main cap fretting on M11 and ISM series engines. This topic includes the following:

- Main cap fretting general information
- Main bearing and bore inspect for reuse guidelines
- Main bearing Plastigage® procedures
- Main bearing condemnation limits
- Loctite® 518 procedures
- Block repair options.

Main bearing capscrew torque procedures:

- Torque-Plus-Angle method
- Torque-To-Yield method.

The following kit part numbers may be used to repair blocks.

| Part Description         | Part Number |
|--------------------------|-------------|
| Service block kit        | 4070793NX   |
| ReCon® service block kit | 4070793RX   |

# Related Procedures

|                                                                      |                                                                                  |
|----------------------------------------------------------------------|----------------------------------------------------------------------------------|
| 101-001-026<br>(/qs3/pubsys2/xml/en/procedures/101/101-001-026.html) | Cylinder Block<br>(/qs3/pubsys2/xml/en/procedures/101/101-001-026.html)          |
| 35-001-006<br>(/qs3/pubsys2/xml/en/procedures/35/35-001-006.html)    | Bearings, Main<br>(/qs3/pubsys2/xml/en/procedures/35/35-001-006.html)            |
| 35-001-999<br>(/qs3/pubsys2/xml/en/procedures/35/35-001-999.html)    | Cylinder Block - Overview<br>(/qs3/pubsys2/xml/en/procedures/35/35-001-999.html) |

---

**Last Modified: 28-Aug-2003**

---