

Fuel Recommendations

⚠ CAUTION ⚠

Due to the precise tolerances of diesel injection systems, it is extremely important that the fuel be kept clean and free of dirt or water. Dirt or water in the system n cause severe damage to both the fuel pump and the fuel injectors.

Cummins Inc. recommends the use of ASTM Number 2D fuel. The use of Number 2 diesel fuel will result in optimum engine performance.

At operating temperatures below 0°C [32°F], acceptable performance can be obtained by using blends of Number 2D and Number 1D.

Note : Lighter fuels can reduce fuel economy or possibly damage the fuel injection pump.

The viscosity of the fuel **must** be kept above 1.3 cSt at 40°C [104°F] to provide adequate fuel system lubrication.

The following chart lists acceptable alternative fuels for ISB Series engines.

Acceptable Substitute Fuels - Cummins ISB Fuel System									
Number 1D Diesel (1) (2) (3)	Number 2D Diesel (3)	Number 1K Kerosene	Jet-A	Jet-A1	JP-5	JP-8	Jet-B	JP-4	CITE
A	OK	A	A	A	A	A	NOT OK	NOT OK	NOT OK

An "A"
means
OK
only if
fuel
lubrici
ty is
adequ
ate.
This
means
the
BOCL
E
numb
er is
3100
or
greate
r as
measu
red
with
the US
Army
scuffin
g
BOCL
E test.

Any
adjust
ment
to
comp
ensate
for
reduc
ed
perfor
mance
with a
fuel
syste
m
using
altern
ate
fuel is
not
warra
ntable.

Winter
blend
fuels,
such
as
found
at
comm
ercial
fuel
dispen
sing
outlet
s, are
combi
nation
s of
Numb
er 1D
and
Numb
er 2D
diesel
fuel
and
are
accept
able.

Additional information for fuel recommendations and specifications can be found in Fuel for Cummins Engines, Bulletin 3379001 (</qs3/pubsys2/xml/en/bulletin/3379001.html>). See ordering information in the back of this manual.