

Fuel Recommendations

⚠ CAUTION ⚠

Due to the precise tolerances of diesel injection systems, it is extremely important that the fuel be kept clean and free of dirt or water. Dirt or water in the system can cause severe damage to both the fuel pump and the fuel injectors.

Cummins Inc. recommends the use of ASTM Number 2D fuel. The use of Number 2 diesel fuel will result in optimum engine performance.

At operating temperatures below 0°C [32°F], acceptable performance can be obtained by using blends of Number 2D and Number 1D.

Note : Lighter fuels can reduce fuel economy or possibly damage the fuel injection pump.

The viscosity of the fuel **must** be kept above 1.3 cSt at 40°C [104°F] to provide adequate fuel system lubrication.

The following chart lists acceptable alternate fuels for B Series engines.

Acceptable Substitute Fuels - Cummins B Fuel System									
Number 1D Diesel (1) (2)	Number 2D Diesel (3)	Number 1K Kerosene	Jet-A	Jet-A1	JP-5	JP-8	Jet-B	JP-4	CITE
A	OK	A	A	A	A	A	NOT OK	NOT OK	NOT OK

Acceptable Substitute Fuels - Cummins B Fuel System		
An "A" means OK only if fuel lubricity is adequate. This means the BOCLE number is 3100 or greater as measured with the US Army scuffing BOCLE test.		

Acceptable Substitute Fuels - Cummins B Fuel System		
--	--	--

Any adjust ment to comp ensate for reduc ed perfor mance with a fuel syste m using altern ate fuel is not warra ntable.	
---	--

Acceptable Substitute Fuels - Cummins B Fuel System			
Winter blend fuels, such as found at commercial fuel dispensing outlets, are combinations of Number 1D and Number 2D diesel fuel, and are acceptable.			
Additional information for fuel recommendations and specifications can be found in Fuel for Cummins Engines, Bulletin 3379001 (/qs3/pubsys2/xml/en/bulletin/3379001.html). See ordering information in the back of this manual.			