

Trainings ▾

Specifications

Automotive Applications

Horsepower

B3.9, B5.9	Refer to engine dataplate
------------	---------------------------

Bore

B3.9, B5.9	102 mm [4.02 in]
------------	------------------

Stroke

B3.9, B5.9	120 mm [4.72 in]
------------	------------------

Displacement

B3.9	3.9 liters [238 C.I.D.]
------	-------------------------

B5.9	5.9 liters [360 C.I.D.]
------	-------------------------

Engine Weight (dry) Less Flywheel and Electric Components

B3.9	308 to 329 kg [679 to 725 lb]
------	-------------------------------

B5.9	388 to 411 kg [855 to 906 lb]
------	-------------------------------

Firing Order

B3.9	1-3-4-2
------	---------

B5.9	1-5-3-6-2-4
------	-------------

Valve Clearance

B3.9 and B5.9

Intake	0.25 mm [0.010 in]
--------	--------------------

Exhaust	0.51 mm [0.020 in]
---------	--------------------

Compression Ratio

B3.9	(rotary pump) 17.6:1
------	----------------------

B5.9	(in-line pump) 17.9:1
------	-----------------------

Crankshaft Rotation (viewed from the front of the engine)

B3.9 and B5.9	Clockwise
---------------	------------------

Aspiration**Turbocharged**

B3.9	Yes
------	-----

B5.9	Yes
------	-----

Aspiration**Charge Air Cooled**

B3.9	Yes
------	-----

B5.9	Yes
------	-----

Industrial Applications

Horsepower	Refer to engine dataplate
------------	---------------------------

Engine Weight (Dry) Less Flywheel and Electronics

B4.5 (naturally aspirated)	326 kg [721 lb]
----------------------------	-----------------

B4.5 and B3.9 (turbocharged)	338 kg [745 lb]
------------------------------	-----------------

B5.9	432 kg [952 lb]
------	-----------------

Compression Ratio	18:1
-------------------	------

Bore

B3.9 and B5.9	102 mm [4.02 in]
---------------	------------------

B4.5	107 mm [4.21 in]
------	------------------

Stroke

B4.5	138 mm [5.42 in]
------	------------------

B4.5 RGT	124 mm [4.88 in]
----------	------------------

B3.9 and B5.9	120 mm [4.72 in]
---------------	------------------

Displacement

B3.9	3.9 liters [238 C.I.D.]
------	-------------------------

B4.5	4.5 liters [275 C.I.D.]
------	-------------------------

B5.9	5.9 liters [359 C.I.D.]
------	-------------------------

Firing Order

B3.9 and B4.5	1-3-4-2
B5.9	1-5-3-6-2-4

Valve Clearance

Intake	0.25 mm [0.010 in]
Exhaust	0.51 mm [0.020 in]
Crankshaft Rotation (viewed from the front of the engine)	Clockwise

Engine Weight (Dry) Less Flywheel and Electronics

B4.5 (naturally aspirated)	326 kg [721 lb]
B4.5 and B3.9 (turbocharged)	338 kg [745 lb]
B5.9	432 kg [952 lb]
Compression Ratio	18:1

Bore

B3.9, and B5.9	102 mm [4.02 in]
----------------	------------------

Stroke

B4.5	138 mm [5.42 in]
B3.9 and B5.9	120 mm [4.72 in]

Displacement

B3.9	3.9 liters [238 C.I.D.]
B4.5	4.5 liters [275 C.I.D.]
B5.9	5.9 liters [359 C.I.D.]

Firing Order

B3.9 and B4.5	1-3-4-2
B5.9	1-5-3-6-2-4

Valve Clearance

Intake	0.25 mm [0.010 in]
Exhaust	0.51 mm [0.020 in]

Crankshaft Rotation (viewed from the front of the engine)	Clockwise
---	------------------

Last Modified: 12-Dec-2019
