

Trainings ▾

Specifications

Oil Pressure

Low Idle (minimum allowed) 69 kPa [10 psi] At Rated Speed (minimum allowed) 207 kPa [30 psi]

Regulated Pressure

B3.9, B4.5, and B5.9 345 kPa [50 psi] B4.5 RGT 448 kPa [65 psi] to 517 kPa [75 psi]

Oil Capacity of Standard Engine

Standard - Oil Pan Only

B3.9 and B4.5 9.5 liters [10 qt] B4.5 RGT 11 liters [11.6 qt] B5.9 14.2 liters [15 qt]

Oil Capacity of Standard Engine

Total System - Standard Oil Pan

B3.9 and B4.5 10.9 liters [11.5 qt] B4.5 RGT 13 liters [13.7 qt] B5.9 16.3 liters [17.2 qt]

Oil Capacity of Standard Engine

Oil Pan Low - High - Standard Oil Pan

B3.9 and B4.5 8.5 to 9.5 liters [9 to 10 qt] B4.5 RGT 9 to 11 liters [9.6 to 11.6 qt] B5.9 12 to 14.2 liters [13 to 15 qt]

Oil Capacity of Standard Engine

Deep Sump - Oil Pan Only

B3.9 and B4.5 14.5 liters [15.3 qt] B4.5 RGT 16 liters [16.9 qt] B5.9 24.0 liters [25.4 qt]

Oil Capacity of Standard Engine

Total System - Deep Sump Oil Pan

B3.9 and B4.5 15.9 liters [16.8 qt] B4.5 RGT 18 liters [19.0 qt] B5.9 26.1 liters [27.6 qt]

Oil Capacity of Standard Engine

Oil Pan Low - High - Deep Sump Oil Pan

B3.9 and B4.5 11.5 to 14.5 liters [12.1 to 15.3 qt] B4.5 RGT 10 to 16 liters [10.3 to 16.9 qt] B5.9 16.5 to 24.0 liters [17.4 to 25.4 qt]

Note : If the type/oil capacity of the oil pan is not known:

1. Contact a local Cummins Distributor/Dealer
2. Determine the capacity of the oil pan option for the engine being serviced by using QuickServe OnLine and the engine serial number
3. Fill the lubricating oil pan to the smallest oil pan capacity listed for the engine being serviced. Then add 0.95 liters [1 qt] of oil at a time until it reaches the high

mark on the dipstick. Record the number of quarts added so that capacity is known the next time the oil is drained.

Last Modified: 21-May-2007
