

Trainings ▾

Specifications

Automotive Applications

Minimum Recommended Battery Capacity @ -18°C [0°F]

12-VDC Starter
With Light Accessories(1)

B3.9 625 CCAB5.9 800 CCA

12-VDC Starter
With Heavy Accessories(2)

B3.9 800 CCAB5.9 950 CCA

24-VDC Starter
With Light Accessories(1)

B3.9 400 CCAB5.9 400 CCA

24-VDC Starter
With Heavy Accessories(2)

B3.9 400 CCAB5.9 475 CCA

Maximum Allowable Starting Circuit Resistance

12-VDC Starter
B3.9 0.0012 ohmsB5.9 0.0012 ohms

Maximum Allowable Starting Circuit Resistance

24-VDC Starter
B3.9 0.0020 ohmsB5.9 0.0020 ohms

- 1. Typical light accessories include alternator, small steering pump, and disengaged clutch.
- 2. Typical heavy accessories include hydraulic pump and torque converter.

Industrial Applications

Minimum Recommended Battery Capacity @ -18°C [0°F]

12-VDC Starter
With Light Accessories(1)

B3.9, B4.5 and B4.5 RGT 625 CCAB5.9 800 CCA

12-VDC Starter

With Heavy Accessories(2)

B3.9, B4.5 and B4.5 RGT 800 CCAB5.9 950 CCA

24-VDC Starter

With Light Accessories(1)

B3.9, B4.5 and B4.5 RGT 400 CCAB5.9 400 CCA

24-VDC Starter

With Heavy Accessories(2)

B3.9, B4.5 and B4.5 RGT 400 CCAB5.9 475 CCA

Maximum Allowable Starting Circuit Resistance

12-VDC 0.001 ohm24-VDC 0.002 ohms

1. Typical light accessories include alternator, small steering pump, and disengaged clutch.
2. Typical heavy accessories include hydraulic pump and torque converter.

Batteries (Specific Gravity)	
Specific Gravity at 27° C [80° F]	State of Charge
1.260 to 1.280	100%
1.230 to 1.250	75%
1.200 to 1.220	50%
1.170 to 1.190	25%
1.110 to 1.130	Discharged