

Trainings ▾

Specifications

Holset® SS296, SS296E, and SS338E A/C Model

A/C Model QE296 Specifications

Compressor Swept Volume at 1250 rpmPiston DisplacementBoreStrokeSpeedCoolingLubrication	6.2 L/sec [13.2 SCFM] 296 cc [18.06 C.I.D.] 92.08 mm [3.625 in] 44.45 mm [1.750 in] 1.135 x Engine rpm Engine Coolant Engine Lubricating Oil
---	--

Plumbing Line Sizes:

Coolant Inlet and Outlet (pipe fitting) 1/2-in NPTF [0.50 in]Air Inlet (inside diameter) 19-mm [0.75-in] NippleAir Outlet (minimum inside diameter) 1/2-in NPTF [0.50 in]

Height, Overall (approximate)Width, Overall (approximate)Length, Overall (approximate)Weight (approximate)	305 mm [12 in] 159 mm [6.25 in] 267 mm [10.5 in] 20 kg [44 lb]
--	--

A/C Model QE338 Specifications

Compressor Swept Volume at 1250 rpmPiston DisplacementBoreStrokeSpeedCoolingLubrication	7.1 L/sec [15 SCFM] 338 cc [20.6 C.I.D.] 98.43 mm [3.875 in] 44.45 mm [1.750 in] 1.135 x Engine rpm Engine Coolant Engine Lubricating Oil
---	---

Plumbing Line Sizes:

Coolant Inlet and Outlet (pipe fitting) 1/2-in NPTF [0.50 in]Air Inlet (inside diameter) 19-mm [0.75-in] NippleAir Outlet (minimum inside diameter) 1/2-in NPTF [0.50 in]

Height, Overall (approximate)Width, Overall (approximate)Length, Overall (approximate)Weight (approximate)	305 mm [12 in] 159 mm [6.25 in] 267 mm [10.5 in] 18 kg [40 lb]
--	--

A/C Model HD650 Specifications

Compressor Swept Volume at 1250 rpm Piston Displacement BoreStrokeSpeedCoolingLubrication	6.2 L/sec [13.2 SCFM] 296 cc [18.06 C.I.D.] 92.08 mm [3.625 in] 44.45 mm [1.750 in] 1.135 x Engine rpm Engine Coolant Engine Lubricating Oil
---	--

Plumbing Line Sizes:

Coolant Inlet and Outlet (pipe fitting) 1/2-in NPTF [0.50 in] Air Inlet (inside diameter) 19-mm [0.75-in] Nipple Air Outlet (minimum inside diameter) 1/2-in NPTF [0.50 in]

Height, Overall (approximate) Width, Overall (approximate) Length, Overall (approximate) Weight (approximate)	305 mm [12 in] 159 mm [6.25 in] 267 mm [10.5 in] 20 kg [44 lb]
--	--

A/C Model HD850 Specifications

Compressor Swept Volume at 1250 rpm Piston Displacement BoreStrokeSpeedCoolingLubrication	7.1 L/sec [15 SCFM] 338 cc [20.6 C.I.D.] 98.43 mm [3.875 in] 44.45 mm [1.750 in] 1.135 x Engine rpm Engine Coolant Engine Lubricating Oil
---	---

Plumbing Line Sizes:

Coolant Inlet and Outlet (pipe fitting) 1/2-in NPTF [0.50 in] Air Inlet (inside diameter) 19-mm [0.75-in] Nipple Air Outlet (minimum inside diameter) 1/2-in NPTF [0.50 in]

Height, Overall (approximate) Width, Overall (approximate) Length, Overall (approximate) Weight (approximate)	305 mm [12 in] 159 mm [6.25 in] 267 mm [10.5 in] 18 kg [40 lb]
--	--

Holset® SS191 A/C Model

A/C Model SS191 Specifications

Compressor Swept Volume at 1250 rpm Piston Displacement BoreStrokeSpeedCoolingLubrication	4.0 L/sec [8.5 SCFM] 191 cc [11.65 C.I.D.] 80 mm [3.15 in] 38.1 mm [1.50 in] 1.135 x Engine rpm Engine Coolant Engine Lubricating Oil
---	---

Plumbing Line Sizes:

Coolant Inlet and Outlet (pipe fitting) 1/2-in NPTF [0.50 in] Air Inlet (inside diameter) 19-mm [0.75-in] Nipple Air Outlet (minimum inside diameter) 1/2-in NPTF [0.50 in]

Height, Overall (approximate) Width, Overall (approximate) Length, Overall (approximate) Weight (approximate)	289 mm [11.4 in] 125 mm [4.9 in] 186 mm [7.32 in] 13.6 kg [30 lb]
--	---

