

Trainings ▾

Specifications

Maintain the following limits (see note) during a chassis dynamometer test:

Intake Restriction (maximum)

Clean Filter:

Light-Duty 254 mm H₂O [10 in H₂O] Medium-Duty 305 mm H₂O [12 in H₂O] Heavy-Duty 381 mm H₂O [15 in H₂O]

Intake Restriction (maximum)

Dirty Filter:

Light-Duty 635 mm H₂O [25 in H₂O] Medium-Duty 635 mm H₂O [25 in H₂O] Heavy-Duty 635 mm H₂O [25 in H₂O]

Exhaust Back Pressure (maximum) Nonautomotive Exhaust Back Pressure (maximum) Automotive with Catalyst Back Pressure (maximum) Automotive without Catalyst	76 mm Hg [3.0 in Hg] 152 mm Hg [6.0 in Hg] to 127 mm Hg [5.0 in Hg] 114 mm Hg [4.5 in Hg] to 102 mm Hg [4.0 in Hg]
--	--

Oil Pressure:

Low Idle (minimum allowable) 69 kPa [10 psi] Rated Speed (minimum allowable) 207 kPa [30 psi]

Fuel Inlet Restriction (maximum) Fuel Return Restriction (maximum)	100 mm Hg [4 in Hg] 518 mm Hg [20.4 in Hg]
---	--

Note : Due to variations in ratings of different engine models, refer to the specific engine data sheet for the particular engine model being tested.