

Trainings ▾

General Information

Perform maintenance at whichever interval occurs first. At each scheduled maintenance interval, perform all previous maintenance checks that are due for scheduled maintenance.

Maintenance Procedures at Daily Interval

- Engine Lubricating Oil Level - Check
- Engine Coolant Level - Check
- Cooling Fan - Inspect
- Drive Belts - Inspect
- Fuel-Water Separator - Drain

Maintenance Procedures at 10,000 Kilometers [6000 Miles], 250 Hours, or 3 Months^{1, 4}

- Lubricating Oil - Change¹
- Lubricating Oil Filters - Change
- Air Cleaner Restriction - Check
- Air Intake Piping - Check
- Charge-Air Cooler - Inspect⁴
- Air Compressor - Check
- Batteries - Inspect
- Radiator Pressure Cap - Check

Maintenance Procedures at 19,000 Kilometers [12,000 Miles], 500 Hours, or 6 Months^{3, 5}

- Fuel Filter (Spin-On Type) - Change⁵
- Antifreeze - Check³
- Cooling Fan Belt Tensioner - Inspect

Maintenance Procedures at 38,000 Kilometers [24,000 Miles], 1000 Hours, or 1 Year²

- Overhead Set - Adjust²
- Drive Belts - Test

Maintenance Procedures at 77,000 Kilometers [48,000 Miles], 2000 Hours, or 2 Years³

- Air Compressor Discharge Lines - Check
- Cooling System - Flush^{3, 6}
- Vibration Damper, Rubber - Inspect

- Vibration Damper, Viscous - Inspect

1. Refer to the oil change interval tables provided in this section to find the specific oil change interval for individual applications.
2. Initial valve lash clearance adjustment, subsequent adjustments to be performed at 77,000 Kilometers [48,000 Miles] intervals or every 8th oil change for automotive engines.
3. Heavy-duty year around antifreeze that meets the critical composition of ASTM D6210 **must** be used. The change interval is 2 years or 320,000 Kilometers [200,000 Miles], whichever occurs first. Antifreeze is essential for freeze, overheat, and corrosion protection.
4. Service interval is 2 years or 320,000 Kilometers [200,000 Miles], whichever comes first.
5. Service interval is every other oil change or 19,000 Kilometers [12,000 Miles], 500 hours, or 6 months, whichever occurs first.
6. The cooling system requirement to Flush at this scheduled maintenance includes: Drain, Flush. and Fill.

Oil Drain Intervals

Refer to the following flowchart to determine the maximum recommended oil change and filter change intervals in kilometers, miles, hours, or months, whichever comes first.

Is the vehicle one of those listed below?

- Is the vehicle an on-highway application?

If Yes -

- Refer to Table 1.

If No -

- Is the vehicle used in a construction, mining, or logging operation?

If Yes -

- Refer to Table 2.

If No -

- Is the vehicle in an agricultural or stationary power application?

If Yes -

- Refer to Table 3.

If No -

- Use the following oil change interval, 10,000 kilometers [6000 miles], 250 hours, or 3 months, whichever occurs first.

Table 1: Use the following oil drain intervals for your application ¹				
Vehicle/Equipment	Kilometers	Miles	Hours	Months
Refuse Truck	10,000	6000	250	3
Mixer/Dumper	10,000	6000	250	3
Delivery Truck	10,000	6000	250	6
Shuttle or Transit Bus	10,000	6000	250	3
School Bus	10,000	6000	250	6
Fire Truck	10,000	6000	250	3
Recreational Vehicle	10,000	6000	250	6
Regional Haul Truck	17,000	10,000	250	3
Coach Bus	17,000	10,000	250	3
¹ Or whichever occurs first. If your application accumulates high hours and low mileage, the change interval is determined by hours.				
Note : If the vehicle accumulates 12,875 kilometer [8000 miles] in a month, the oil change interval will be 17,000 kilometer [10,000 miles] or 250 hours, whichever occurs first.				
Table 2: Use the following oil drain intervals for your application ¹				
Vehicle/Equipment	Kilometers	Miles	Hours	Months
Truck Crane	10,000	6000	250	3
Yard Spotter	10,000	6000	250	3
Paver	N/A	N/A	250	6
Cranes	N/A	N/A	250	6
Backhoe	N/A	N/A	250	6
Dozer	N/A	N/A	250	6
Scraper	N/A	N/A	250	6
Skidder	N/A	N/A	250	6
¹ Or whichever occurs first. If your application accumulates high hours and low mileage, the change interval is determined by hours.				
Table 3: Use the following oil drain intervals for your application ¹				
Vehicle/Equipment	Hours	Months		
Farm Tractors	250	6		
Combines	250	6		
Irrigation Equipment	250	6		
Generator Set	250	6		

Table 3: Use the following oil drain intervals for your application ¹		
Vehicle/Equipment	Hours	Months
Air Compressor	250	6
Fire Pump	250	6
Pleasure Boat	250	6
Work Boat	250	3
¹ Or whichever occurs first. If your application accumulates high hours and low mileage, the change interval is determined by hours.		