

Trainings ▾

Specifications

Maximum Starting Circuit Resistance:

24-VDC starter 0.00200 ohm

Battery Cable Sizes - American Wire Gauge (maximum length in cranking motor circuit) 24 to 32-VDC

Number 00 6.1 m [20 ft] Number 000 8.2 m [27 ft] Number 0000 or two Number 0* 10.7 m [35 ft] Two Number 00 13.7 m [45 ft]

Minimum Cranking Speed without Starting Aid	130 rpm
---	---------

* Two strands of Number 0 cable can be used instead of one Number 0000 cable, provided that all connections are carefully made to provide equal current flow in each parallel cable.

Note : Starting aids, such as block heaters, lubricating oil pan heaters, and so forth, are available to aid in cold weather starting.

System Voltage	Ambient Temperatures			
	-18°C [0°F]		0°C [32°F]	
	Cold Cranking Amperes	Reserve Capacity* Amperes	Cold Cranking Amperes	Reserve Capacity* Amperes
24 VDC**	900	320	640	240

* The number of plates within a given battery size determines reserve capacity. Reserve capacity is the length of time sustained cranking can occur.

** CCA ratings are based on two 12-VDC batteries in series.

Battery State of Charge	Specific Gravity @ 27°C [80°F]
100%	1.260 to 1.280
75%	1.230 to 1.250
50%	1.200 to 1.220
25%	1.170 to 1.190
Discharged	1.110 to 1.130

Last Modified: 16-May-2007
