



Technical Service Bulletin

Technical Service Bulletin: tsb100741

Released Date: 24-Sep-2008

QSK23 Tier 2 Engine Introduction

QSK23 Tier 2 Engine Introduction

Warranty Statement

The information in this document has no effect on present warranty coverage or repair practices, nor does it authorize TRP or Campaign actions.

Contents

The purpose of This Technical Service Bulletin is to introduce the QSK23 Tier 2 Engine (engine family 89). The QSK23 is a 23 liter, 4-valve head, 1 pump-1 loop, air-to-air charge air cooler (ATA-CAC), inline 6-cylinder diesel engine, certified to U.S. EPA Tier 2 emissions. The QSK23 fills the horsepower node between the QSK19 and QST30, with ratings between 760 to 950 hp for industrial applications, and 880 and 1220 hp for power generation applications. This engine is fully electronically controlled, with a displacement of 23.15 liters [1413 cu in] targeted at various applications within the mining, construction, and power generation markets. The QSK23 is a Cummins® branded engine and all current Cummins Inc. warranty coverages and guidelines apply.

Engine Envelope/Weight Comparison

	QSK23 Cummins® Turbo Technologies Turbocharger Tier 2	QSK23 Schwitzer Turbocharger
Height above Crankshaft Centerline	1159 mm [45.6 inch]	1133 mm [44.6 inch]
Overall Engine Height	1720 mm [67.7 inch]	1694 mm [66.7 inch]
Overall Length - Rear of flywheel housing to fan mounting pilot face	1939 mm [76.3 inch]	1939 mm [76.3 inch]
Overall Width	1046 mm [41.2 inch]	1068 [42 inch]
Weight (dry - lbs)	2858 kg [6300 lb]	2858 kg [6300 lb]

Training for the QSK23 Tier 2 is contained in Cummins® Virtual College training modules. This will be part of the High Horsepower Virtual College.

